



AMERICAN CAR CRAFT INSTRUCTIONS

HHR BRUSHED STAINLESS TAILLIGHT TRIM

PART#422016

PARTS INCLUDED:

- ___ 4-Stainless Taillight Trim Rings (marked Driver and Passenger)
- ___ 2-Adhesive Promoter Tube

1. These stainless rings attach to the painted surface around each taillight lens. Thoroughly clean the perimeter of the taillight lens with household rubbing alcohol to remove any dirt and wax. Then swipe each of the four areas once with the adhesive promoter tube provided.
2. Your new rings come to you in a package marked driver and passenger. Remove the rings from either side and you will notice that the rings are not quite a perfect circle. These are made this way so that they will match the irregular shape of the lens. The top lenses are slightly different than the bottom ones so you will simply need to place the ring over the lens and rotate it until the shapes match. Once you have matched the ring mark the lenses and the rings with a grease pencil or china marker so that you will be able to reestablish the positions of each ring when you are ready to permanently attach the ring to the paint.
3. Now that you have established the correct position of each ring simply peel the red release liner from the back of each ring and carefully place them onto the paint and press firmly to set in place. **DO NOT GET WET FOR 24 HOURS.**



Thank you and enjoy your purchase!

Note: EXTRA CARE must be taken when cleaning your stainless kit. It is a good idea to lightly dust your kit with a clean soft cloth first in order to prevent any particles from scratching it. Then wipe (using a new clean soft cloth) with a good quality streak free glass cleaner.