



AMERICAN CAR CRAFT INSTRUCTION

2008-2010 Dodge Viper Valve Cover Letter Set
PART#973016



PARTS INCLUDED:

2-VIPER Letter Sets

1-Promoter Packet

- 1. You should have pieces that spell out "VIPER" for each Valve Covers. Ten pieces in all.**
- 2. When your engine is cool to the touch wash the area on your engine Valve Cover where you are going to mount the letters.**
- 3. Set each number on top of Cover to see how it fits.**
- 4. Once you are comfortable with how each letter fits take your promoter packet or pen and open it (you must snap the pen at its midpoint to initiate it). Wipe down the raised 3-D letters on the Valve Covers where you are going to mount your new stainless steel letters.**
- 5. Let dry for 2 minutes. Remove the back off one letter at a time and place it on top of the Valve Cover where it goes. Press firmly all along the surface of the each Letter.**
- 6. If your letters have a clear plastic protective seal on top of Them, you may peel it off at this time.**

7. Let sit overnight.

8. Clean with a good glass cleaner as needed.

Note: Care must be taken when cleaning your sills. It is a good idea to lightly dust your sills with a clean soft cloth first in order to prevent any particles from scratching them. Then wipe (using a new clean soft cloth or bounty paper towel) with a good quality streak free glass cleaner.

Thank you and enjoy your new purchase!