



Addictive Desert Designs

2015 – Current F150 HoneyBadger Rear Bumper Installation Instructions

PREPARATION

1. Disconnect the negative terminal on the battery. Park the vehicle on level ground and set the emergency brake.
2. We recommend reading through the installation instructions in whole before performing the work.
3. You will need the following tools:
 - a. 13mm Socket
 - b. Ratchet
 - c. 3/4" Socket and Wrench
 - d. 11/32" Drill Bit

Note: this installation requires 2 people for best results


4. Included in Kit:
 - 6 – Hex Head Bolts – 1/2"-13 x 1 1/2"
 - 12 – Flat Washers – 1/2"
 - 6 – Nylon Locking Nuts – 1/2"-13
 - 1 – Trailer Plug Relocation Bracket
 - 2 – 3/8"-16 Hex Head Thread Cutting Bolts

REMOVAL

1. Remove the license plate light sockets from their housings.
2. Remove the license plate light housings from the bumper by gently pulling them outwards.
3. Unplug the electrical connector for your trailer/towing lights.
4. Remove the trailer light plug by pushing in the tabs on the back of the assembly and pushing the assembly out of the front of the bumper.
5. Remove the spare tire access lock, if equipped, by turning the key to the unlocked position and pulling the assembly outwards.
6. If equipped with parking sensors, remove them by spreading the two tabs on the rear of the outer ring and pushing the sensor out of the backside of those rings. Refer to Fig A.



7. Pull the black plastic piece off of the top of the rear bumper. There are no tools necessary for this step, it will pull off by hand. This part has been labeled as "A" in Fig B.
8. Next, remove the 13mm bolts (x10) holding the two metal portions of the bumper to the frame. These portions have been labeled as "B" and "C" in Fig B. Fig C points out the locations of the bolts that hold them on (there are 5 bolts per piece).




9. Remove the parking sensor outer rings by pushing the two tabs on the back of the ring in and pushing the ring out of the front of the bumper.
10. You are now ready to start the installation of your new A.D.D. Rear bumper.

INSTALLATION


1. Bend back the bracket that used to house the trailer light plug as shown in Fig D.




2. Line the 6 mounting holes on the back side of your A.D.D. HoneyBadger Rear Bumper with the 6 mounting holes on the rear of your truck frame. Refer to Fig E.



3. Use the supplied 1/2"x1 1/2" Bolts (x6), 1/2" Washers (x12), and 1/2" Locking Nuts (x6) to secure the bumper to the frame mounts. Leave all bolts finger tight.
4. Align the bumper so that it sits straight in relation to the bottom of the tailgate. Also make sure it is aligned left to right. Torque the mounting bolts to 70 foot pounds.
5. Install the license plate light fixtures onto your bumper by pushing them into their mounting holes. Refer to Fig F.
6. Connect the license plate light sockets to the housings. Refer to Fig G.




7. If you have lights for your bumper, now is a good time to install them. Refer to Fig H.
 - a. Fit the threaded post on the bottom of the light into the mounting hole
 - b. Tighten the nut to the light manufacturer's specification
 - c. To wire the lights, please follow the light manufacturer's instructions



8. Install the spare tire access lock by turning the key to the unlocked position, pushing the lock into its mounting hole, turning the key to the locked position, and removing the key. Refer to Fig I.



9. Install the trailer plug relocation bracket.
 - a. Choose a spot to mount the bracket. We chose to the left of the hitch. Refer to Fig J.
 - b. Using the adapter as a template, drill 2 holes with an 11/32" bit.
 - c. Install the supplied 3/8"-16 Thread Cutting Bolts (x2).
 - d. Push the trailer plug into the relocation bracket and connect the electrical connector.



10. Install the parking sensors.
 - a. Push the outer mounting rings into the holes cut into the bumper.
 - b. Push the sensors into the outer ring from the back. Refer to Fig K.
 - c. With the HoneyBadger Rear, we recommend using a zip tie to hold the parking sensor wires in a bundle or they might hang down lower than your bumper.



11. Stand back and enjoy your A.D.D. HoneyBadger Rear Bumper.
12. Check and re-tighten if needed, all mounting bolts after 100 miles and periodically thereafter.

