

Intake kit Installation Instructions: 2005-2007 Chevrolet Corvette C6 V8-6.0L LS2 Stage 2

Kit P/N:	51/54-109	02	Tools Required:	<u>Parts list:</u> 1 Air filter(Pro-5R ™ 24-90033
			5/16" nut driver	Pro Dry S™ 21-90033)
Make:	Chevrolet		Flat head screwdriver	1 Tube, rotomold
Model:	Year:	Engine:		1 Coupler, reducer (4" x 3-1/2" X 3-1/2")
	6) '05-'07	V8-6.0L LS2		1 Clamp, #072
00.700 (0	.,			2 Clamp, #060
				1 Cap, 3/4"
				- 1 ,





Complete Stock Intake.



Disconnect MAF sensor harness and vacuum line. Loosen clamps with 5/16" nut driver.



Lift up air box carefully from middle. Pull back MAF sensor from OE tube.



Take air box out of vehicle.




Remove OE tube with MAF sensor.



Remove OE plastic fitting from tube and install into new coupler.



Install MAF sensor to inside of tube with clamp. Do not tighten.



<u>Install air filter</u> and tighten with 5/16" nut driver. Place 3/4" cap through hole on filter.



Install coupler to throttle body using clamps provided. Place tube to factory position and install completely . Do not tighten.



Tighten all clamps using 5/16" nut driver.



Re-connect MAF sensor harness and vacuum line.



Place enclosed CARB EO sticker on a clean/smooth surface on or near the intake system. EO identification label is required in passing the Smog Check Inspection. You ristallation is now complete. Please check all boils and clamps periodically. Re-tighten if necessary. Thank you for choosing aFe!