

# 60 / 40 / 20 TON **SUPER DUTY** 3 STAGE AIR / HYDRAULIC AXLE JACK



#### Model 548SD

- This SUPER HEAVY DUTY, 3 Stage 60/40/20 Ton Air Hydraulic Jack covers a wide variety of demands from the Heavy Duty Trucking, Agricultural, Fleet, Construction and Military sectors
- The piston head seal design is borrowed from Industrial technology providing a superior low and high pressure seal, giving this jack a much better hold under severe load conditions
- The extra long 138cm (54") handle can be locked in 3 positions for easy positioning of this jack in hard to reach places.
- An integral Descent Metering Valve maintains a controlled and safe lowering of the load
- Single piece base construction provides superior strength for increased load stability
- Double polished chromed pistons allow for much tighter tolerances which reduce oil bypassing and reduced ram scoring
- · Air assisted lowering speeds up ram retraction
- Built in overload safety valve prevents damage to unit due to excessive load
- Comes with 2 extensions (75mm/3" + 45 mm1.75") and saddle adapter
- Units are tested to -13F(-25C) and +113F(+45C) as well as off center loading to ensure a long life under even the harshest conditions

### **Specifications:**

60 Ton (1st Stage)

- Low Height: 175 MM (6.89")
- High Height: 252 MM (9.92")
- Lift 77 MM (3.03")

40 Ton (2nd Stage)

- Low Height: 175 MM (6.89")
- High Height: 322 MM (12.68")
- Lift 147 MM (5.79")

20 Ton (3rd Stage)

- Low Height: 175 MM (6.89")
- High Height: 404 MM (15.91")
- Lift 229 MM (9.02")
- Working Air Pressure
  0.8 to 1.2 Mpa (116 to 174 psi)
- Net Weight: 73 kgs (161 lbs.)
- Shipping Weight: 75 kgs. (165 lbs.)

## RELATED PRODUCTS



**Model 545SD** 30/15 Ton 2 Stage



**Model 546SD** 25/10 Ton 2 Stage



Model 548SD 60/40/20 Ton 3 Stage



**Model 549SD** 80/50 Ton 2 Stage