

Single Pass Aluminum Radiators

Excellent quality at an affordable price. Filler necks are machined, not stamped, and water tanks are furnace brazed, not epoxied, eliminating two prime sources of leakage. The lightweight 1" tubes, arranged in two rows, offer outstanding cooling in Ford and GM powered race cars, off-road vehicles and street machines. Standard 1-1/2" inlets and 1-3/4" outlets have beaded hose fittings. Aluminum radiators are available in 22", 24", 26", 28", and 31" overall widths (including tanks) to fit a wide variety of chassis and engine compartment configurations.

GM		
Radiators:	Core Size	Overall
ALL30010	17" W x 18" H	22" x 19"
ALL30011	19" W x 18" H	24" x 19"
ALL30012	21" W x 18" H	26" x 19"
ALL30014	23" W x 18" H	28" x 19"
ALL30016	26" W x 18" H	31" x 19"
ALL30042	23" W x 15" H	28" x 16"

Ford/Chrysler			
Radiators:	Core Size	Overall	
ALL30020	17" W x 18" H	22" x 19"	
ALL30021	19" W x 18" H	24" x 19"	
ALL30022	21" W x 18" H	26" x 19"	
ALL30024	23" W x 18" H	28" x 19"	
ALL30026	26" W x 18" H	31" x 19"	
ALL30043	23" W x 15" H	28" x 16"	



Replacement Part:

ALL99312......Overflow Fitting 1/8" NPT to 5/16" Hose

REV082917