

Primary Wire

Single conductor stranded copper wire with polyvinyl insulation which remains flexible and is abrasion resistant. Stranded copper is the wire of choice for many projects when building custom wire harnesses or adding accessories.

| 20AWG | Color | 50' Coil | 100' Spool |
|--|--------|----------|------------|
| Used for low voltage sensors, indicator lights, instrument panel or dash lighting. | Red | ALL76500 | ALL76510 |
| | Black | ALL76501 | ALL76511 |
| | White | ALL76502 | ALL76512 |
| | Green | ALL76503 | ALL76513 |
| | Yellow | ALL76504 | ALL76514 |
| | Brown | ALL76505 | ALL76515 |
| | Blue | ALL76506 | ALL76516 |
| 14AWG | Color | 20' Coil | 100' Spool |
| Most popular when fabricating harnesses for general use in- cluding lighting of headlights, taillights and brake lights, ignition systems and interior accessories such as radios, in- terior fans and gauge panels. | Red | ALL76540 | ALL76550 |
| | Black | ALL76541 | ALL76551 |
| | White | ALL76542 | ALL76552 |
| | Green | ALL76543 | ALL76553 |
| | Yellow | ALL76544 | ALL76554 |
| | Brown | ALL76545 | ALL76555 |
| | Blue | ALL76546 | ALL76556 |
| 12AWG | Color | 12' Coil | 100' Spool |
| Wire can be used to supply power to ignition boxes, cool- ing fans, fuel pumps and other higher amperage accessories including power to electric trailer brakes. | Red | ALL76560 | ALL76565 |
| | Black | ALL76561 | ALL76566 |
| | White | ALL76562 | ALL76567 |
| | Blue | ALL76563 | ALL76568 |
| 10AWG | Color | 10' Coil | 75' Spool |
| Commonly used for higher | Red | ALL76570 | ALL76575 |
| amperage applications includ- ing alternator charging wire and supplying power to trailer for interior lighting or charging trailer batteries when utilizing tow vehicle charging system. | Black | ALL76571 | ALL76576 |
| | White | ALL76572 | ALL76577 |

REV092412