

GENERAL INSTALLATION INSTRUCTIONS Universal Clear LED Replacement Taillight Part # 861037

Installation Notes:

- 1. Please read the special instructions section at the bottom of the instructions to determine the correct parts needed for your installation.
- 2. Please read all instructions before installing.
- 3. The following procedure describes a generic (typical) installation.
- 4. Prior to installation check all parts and inspect for damage and/or cracks
- 5. Lighting laws vary depending on the jurisdiction, check your local laws before installation.
- 6. Consult your local mechanic or technician if uncertain of wiring or installation.

Installation:

- 1. Remove the stock light from the vehicle
- 2. Take the Anzo light out of the package and remove the front cover
- 3. Set the stock light and the Anzo light next to each other face down
- 4. With your screw driver punch out the correct mounting holes on the back of the Anzo light
- 5. Flip the Anzo light back over and pull the center portion up and out
- 6. Insert the supplied mounting bolts into the holes you punched out
- 7. Mount the light onto the vehicle
- 8. Replace the center section back in the light housing and bolt the cover in place

Wiring:

- 1. Splice the red wire into the reverse wire (not required on some vehicles)
- 2. Splice the brown wire into the driving/running light wire
- 3. Splice the yellow wire into the brake/turn signal wire.

Check the light for proper function after installation.





Special Instructions:

For 87-95 Jeep Wrangler you will need to upgrade your turn signal flasher to a LL552 flasher in order for the lights to work properly. This flasher is available at any local auto part store.



Your flasher is located under the steering column on the firewall.

For 97-2006 Jeep Wrangler use the supplied resistor.



Connect one side of the resistor to the plate The other end of the resistor will get Inside the taillight assembly.

spliced in with the brake/turn signal wire.

Be sure to test all functions of the light before operating your vehicle on the highway.