

Ι

Part#	GR01GFG61H			Application		06~1	06~10 Cadillac DTS – Main Upper Stainless Steel Mesh Grille							
		Item	Par	t Na	ame QTY		Description		Item	Part Name		QTY	Description	
		1	Mesh Gr	rille		1	Stainles	s steel	5	K-Lock Nuts		6	6-32	
Parts L	.ist	2	Plastic F	Push	Clips	Clips 4		6-32×1 ″		Center Logo Plate		1		
		3	Top Plate			1			7	Flange Nuts		2	10-32	
		4	Counters	sunk	Screws	2	1″							
Install N	Note	es: Ov	verlay 🔽 Rep			lacem	ment 🗸 [Cut	×			
Step	Description						illustration							
1	Identify the grille & hardware with parts list.													
2	You may need to remove the black plastic cover (at the bottom of OEM front bumper) from vehicle. This will allow access to the rear of the grille shell.Set the factory grille aside. Remove the factory Cadillac logo from the grille using a heat gun and fishing line.													
3	Locate your new mesh insert. Place the top plate onto the grille and secure it to the grille using the provided K-Lock nuts. Locate the new logo center plate.Secure it to the grille using the counter sunk screws, washers and k-lock nuts. Center the grille into the grille opening. Slide the lower tabs into the bumper slots. Place the provided push in clips into the holes in the lower tabs Place the factory logo onto the new center plate. If the logo is centered; apply pressure to the logo until it adheres to the plate. If logo does not adhere; replace the two sided tape on the rear of the logo.													
4	Secure the stud to the threaded holes on the rear of the grille.								N/A					
5	Center the grille into the opening of the factory grille shell. Be sure the Screws are through the OEM grille shell.							N/A						
6	Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell.							N/A						
7	Make sure the grille is centered and tighten the fasteners.							N/A	N/A					
8	Reinstall the black plastic cover which was removed in step 2.							N/A	N/A					
9	Ins	tallation	complete	ed!!!				N/A	N/A					

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!