



PATENT PRODUCT





Grille Installation Instruction

Rev. 190601

| | | |
|-------|----------------------------|---|
| Part# | <i>GR04FFJ32 C/J/S</i> | For 2015-2018 Dodge Charger Main Upper (Only for Daytona and RT SCAT pack and Daytona 392 and SRT 392 and SRT Hellcat) / 2019 Dodge Charger Only for GT and RT |
|-------|----------------------------|---|

| Parts List | Item | Part Name | QTY | Description | Item | Part Name | QTY | Description |
|------------|------|---------------|-----|-----------------|------|------------|-----|-------------|
| | 1 | Billet Grille | 1 | Stainless steel | 3 | Toggle Nut | 5 | 6# -32 |
| | 2 | Bolt | 5 | 6#-32x1.5" | | | | |

Install Notes: Overlay Replacement Drill Cut

| Step | Description | illustration |
|------|--|---|
| 1 | Identify the grille & hardware with parts list. |  |
| 2 | Optional: remove the plastic cover on the bottom of the OEM front bumper, which will allow access to the rear of the OEM grille | |
| 3 | Insert the screws into the weld tab hole from front side of the billet grille. | <div style="display: flex; align-items: center;"> <div style="border: 1px solid black; padding: 5px; margin-right: 10px;"> Picture for reference only. This is not actual grille. </div> <div style="text-align: center;">  </div> </div> |
| 4 | Center the billet grille onto the OEM grille. Press & insert the toggle nuts on to the rear of the OEM grille through the gap between the horizontal bars. | |
| 5 | Secure the grille using the toggle nuts and screws from the front side of the billet grille with a screw driver. | <div style="text-align: center;">  </div> |
| 6 | Installation completed!!! |  |

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!