

3

Step 2: Factory Grille

Shell Removal Stud

Flat Tabs

## Grille Installation Instruction

Part#	GR04GAA99T			2011-2014 Dodge Charger (Not For SRT Model And Adaptive Speed Control(NHP) Package)				
	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Mesh Grille	2	Stainless steel	5	Lock Nut	14	6-32
Parts List	2	Stud	4	6-32×3″	6	Flat Washer	4	Φ25×Φ5×1

Flange Bracket

Screws

**Install Notes: Overlay** Replacement Drill Cut

6

6-32×1"

#### Installation

8

Identify the grille insert & hardware with parts list Step 1



Step2-1: Pop hood, Remove 2 Plastic Covers Step2-1: Remove 4 Clips along the Factory Grille above the Factory Grille Shell.



4

6-32×1"

Shell.



Step2-3: Remove 2 Clips along the Fender.



Step2-4: Use a Plastic Prybar to seperate the Fender Cover from Bumper Shell and remove 10mm Bolt.



bumper, Carefully pull the side bumper outward to Bumper Shell. release clips.



Step2-5:On each end, Clips secure the side Step2-6:Remove 6 Bolts along the bottom of the

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!

## Grille Installation Instruction

2011-2014 Dodge Charger (Not For SRT Model And Adaptive Part# GR04GAA99T Speed Control(NHP) Package) Step2-7:Remove factory grille and bumper (grille and bumper are connected together) Step3-1: Remove 6 Screws from around the Factory Grille and 1 Screw on the Bumper Support. Step3-2:Remove Bumper Support. Step 3: Grille Removal Step3-3:Unclip 16 clips from around the Factory Step3-4: Remove Factory Grille. Grille. Step3-6: Unclip the Dodge Logo on the Factory Grille. Step3-5:Unclip 8 Clips from around the OEM Grille Shell and remove (OEM Grille Shell will come out from front).

## Grille Installation Instruction

2011-2014 Dodge Charger (Not For SRT Model And Adaptive Part# GR04GAA99T Speed Control(NHP) Package) 4-32×1" Step4-2:Center the grille into the opening of the factory grille shell,Be sure the studs are through the OEM grille shell. 4-32×3" Step4-1:Secure the sud to the threaded holes on the rear of the grille. Step 4: Grille Installation Step4-3: On the 4 short studs on the Grille Shell, Insert Flange Brackets to so it latches onto Step4-4:Place back the Factory Grille over the Grille the Factory Grille Shell and thread a Lock Nut in Shell. Place. Step4-6: Place back the Bumper Filler and re-install the 3 Screws along the bottom of the Factory Grille. Step4-5:Place 4 Flat washers Around the Threaded Screws on the Grille Shell and thread Lock Nuts in Place. Step4-7: Re-Assemble Bumper Support, Clips and bolts.

# Grille Installation Instruction

Part#	GR04GAA99T	2011-2014 Dodge Charger (Not For SRT Model And Adaptive Speed Control(NHP) Package)					
Step 5: Bumper Grille Installation	Move on to the bumper grille. Thread a screw in each nut welded to the grille. From the rear, place a tab on each screw. Now thread a nut on each screw.						
	Center the grille into the opening of the factory grille shell. Secure the bolt to the threaded holes on the front of the grille. Be sure the bolts are through the OEM grille shell.						
	Secure grille using the k-lock nuts from the back side of the OEM grille shell.						
	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.						
Installation completed!!							