

8

Installation completed!!!

Grille Installation Instruction Rev. 190401 Part# GR04GFH70T/H For 2011-2014 Dodge Avenger Application **Part Name QTY Description** Item **Part Name Item** QTY Description **Parts List** 1 Mesh Grille 4 Stainless steel 3 K-Lock Nut 6-32 12 2 Flat Tab 12 4 6-32×1" stud 12 X X Install Notes: Overlay Replacement Drill Cut Step **Description** illustration 1 Identify the grille & hardware with parts list. Optional (for vehicles with black plastic cover under hood). Pop hood, remove the black plastic cover (on top of OEM grille / 2 front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation. 3 Secure the stud to the threaded holes on the rear of the grille. 4 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.. Secure grille using the flat tabs and lock nuts from 5 the back side of the OEM grille shell. Make sure the grille is centered and tighten the fasteners. Please remove the Dodge logo trademark from OEM shell if 6 necessarily. 7 Reinstall the black plastic cover which was removed in step 2.

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!