



Grille Installation Instruction

Part#	GR04HEC44C&J&S	Application	For 2005-2007 Dodge Dakota
--------------	----------------	--------------------	----------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	2	Stainless Steel	2	Rivets	8	1/8" × 3/4"

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Open the hood and remove the grille shell from the vehicle. Remove the 12 retaining nuts and screws from the grille shell assembly. Place the grille shell face down on a work surface. Use a razor knife or wire cutter to cut the center plastic bars from the opening in the factory grille inserts. Do not remove the insert assemblies; just cut the center bars where they contact the outer plastic. Each opening will require 3 cut on top /bottom and 4 cuts on each end.	
3	The passenger side upper billet has a notch to allow access to the hood latch assembly. Center this billet into the openings. The mounting brackets rest next to the factory insert mounting tabs. The tabs align to the soft plastic outer ring. Drill a 1/8" hole at each mounting hole. Use the 1/8" rivets to secure the billets in place. Repeat this process on the drives side.	
4	Make sure the billet grille is centered and tighten the fasteners.	
5	Reinstall the black plastic cover which was removed in step 2.	
6	Installation completed.	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.
 Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.
 We are not responsible for any damage caused by the installation. Thank you for choosing our product!