

Grille Installation Instruction

Part# GR06DEG27A/H Application For 2004-2008 Ford F-150 Honeycomb Style With Logo Show Not For FX2/FX4 and King Ranch Model

	For FX2/FX4 and King Ranch Model										
		Item	Part Nam	e QTY	Description	Item	Part Na	me	QTY	Description	
Parts L	ist	1	Grille	1	Stainless steel	3	Nylon Lock N	uts	4	6#	
		2	Studs	4	6-32×1.5 "	4	Flat Tabs		4		
Install N	Note	es: Ov	verlay √	Replace	ment ×	Drill	× Cut	×			
Step	Description					illustration					
1	Identify the grille & hardware with parts list.								>		
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.										
3	Thread a stud in each nut welded to the grille. From the rear, place a tab on each screw. Now thread a nut on each screw.										
4	Mal	Make sure the grille is centered and tighten the fasteners, but do not over-tighten.									
5	Reinstall the black plastic cover which was removed in step 2.										
6	Inst	tallation	completed!!!			STU	5 5 72 1 5260	5350	्राम् 		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!