

## Grille Installation Instruction

Part#	GR0	6DFC10D	Appli	catior	For 2015	-2017 F	Ford F-150 Main U	Jpper	
	Item	m Part Name		QTY	Description	Item	Part Name	QTY	Description
Parts List	. 1	Mesh Grille		1	Stainless steel	4	Fender Washers	7	
rails Lis	2	"Z" Brackets (Long)		2		5	Nylon Lock Nuts	14	10-24
	3	"Z" Brackets (Short)		3					
Install Notes: Overlay $\times$ Replacement $\sqrt{}$ Drill $\times$ Cut $\times$									
Step	Description illustration								
	Identify the grille & hardware with parts list.								
2	Turn off engine and chalk tires with stop block . Open Hood.								
	Identify & locate (10) plastic clips on top of plastic shroud and also (1) additional on each side located at the top of the headlight body panel cover. Carefully pry off to remove and then set aside for reinstallation later.								
	Remove plastic shroud and then set aside for reinstallation later.								
	FIG 1								
	On the inside of the inner wheel well lip, remove (2) 7mm bolts. The headlight plastic body panel should now loose. You will need to coax panel out and off catch tabs to remove completely. The plastic wedge spatula should help.  FIG 4  FIG 5								

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.



FIG 10

## Grille Installation Instruction

Part#	GR06DFC10D Application For 2015-2017 Ford F-150 Main Upper					
6	On each side of the factory grille near the bottom corner just outside and behind, there is (1) 8mm bolt, (1) 8mm bolt on each side. Use 8mm socket to remove the (2) bolts.  FIG 6					
7	On top of the core support, remove (4) 8mm bolts.	(4) 8mm				
8	Remove (4) plastic clips on upper corner near ead lamp.					
9	Located next to the hood latch, disconnect (2) sensors located at the top center of grille. Note to pull the plastic cable support clip.					
10	The OEM Factory Grille should now be free and ready to remove. Carefully place the grille on a soft cushioned surface and prepare to remove the shutter component which is currently fastened to the backside of the factory grille.					
11	Remove the (7) 10mm plastic bolts that line the outside edge and the (1) 8mm bolt that is secures the center structure.					
12	Remove the (4) plastic clips located on the top lip.					
13	Set factory grille aside and prepare to install your new Grille.					

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.



## Grille Installation Instruction

Part#		GR06DFC10D	Application	For 2015-2017 Ford F-150 Main Upper		
14	With the new grille unit placed face down on a flat cushioned surface.  Set all extension brackets in place starting with large bracket on the lower bottom corners and the small brackets in the middle. Secure and fasten them with 10mm nuts.					
		FIG 12		FIG 13		
15	w	einstall shutter com ith factory hardware moved.				
16	a	ip up and stand the ccess top. Re-insert an secure shutter co	plastic clips whi	ch will		
Grille assembly is now ready to reinstall on vehicle. Match it up to factory mounting points and reinstall in the reverse order that the grille was removed. Start with the (4) 10mm factory bolts on top and the (2) 8mm bolts located near the bottom corners.						

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

**FIG 16** 



## Grille Installation Instruction

Part#		GR06DFC10D	Application	For 2015-2017 Ford F-150 Main Upper			
18		ug the (2) sensor cor mponent sensor unit		nto the shutter			
19	Place plastic radiator shroud cover over core support making sure the cold air intake lip is overlapped on top of the shroud. Align the factory mounting holes and use the (10) plastic clips to secure and fasten in position						
20	Carefully put back into place the headlight plastic body panel around the head lamp area making sure to align with 8 tab fasteners and then firmly press into place. Use the (2) bolts to mount and secure the panel on the inside wheel well lip. on each side of the grille at the top corners, reinsert the plastic tabs. (1) on each side						
21	Reinstall the plastic shroud with the fasteners removed in Step 4.						
22	Installation completed!!!						

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.