

Grille Installation Instruction

Part#	G	GR06GEC27T Application 08-10 F Grille				Ford I	ord F250/F350 Pickup – Stainless Steel Mesh					
		ltem	Part Name		QTY	Description		ltem	Part Name	QTY	Description	
Parts L	ict	1	Mesh Grille		6	Stainless steel		4	2-Hole Tabs (Long)	8		
	2		Screws		22	6-32×1″		5	2-Hole Tabs (Short)	6		
		3 K-Lock Nuts			22	6-32						
Install Notes: Overlay \checkmark Replacement \times								orill ×	Cut ×			
Step		Description						illustration				
1	Identify the grille & hardware with parts list.)		
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow N/A access to the rear of the grille shell.											
		cure the grille.	stud to the	e threaded	holes or	n the rear	of					
3	she	Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.										
4	Se of t	Secure grille using the lock nuts from the back side of the OEM grille shell.						N/A				
5		Make sure the billet grille is centered and tighten the fasteners.but do not over-tighten.						N/A				
6		Reinstall the black plastic cover which was removed in step 2.						N/A				
7	Ins	Installation completed!!!						N/A				

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!