

Grille Installation Instruction

Part#	G	GR06GEG27T/H			Annucation			or 2004-2008 Ford F-150 (With OE Honeycomb Style rille, Not for Bar Style)				
	lt	tem	Part Name		QTY Descrip		tion	Item	Part Name	QTY	Description	
Parts List		1	Mesh Grille		1 Stainless s		ss ste	eel	3	Studs	4	10-24 X 2″
		2	Flat tabs		4				4	Nuts	4	10-24
Install	Notes	otes: Overlay \checkmark			Replacement ×] D i	rill 🖂	Cut	×	
Step	Description							illustration				
1	Identify the grille & hardware with parts list.							N/A				
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.											
3	Test fit the grille to make sure that it fits in the shell properly.											
4	Thread a screw in each nut welded to the grille. Center the grille into the opening of the factory grille shell. Be sure the bolts are through the OEM grille shell.											
5	From the rear, place a tab on each screw. Now thread a nut on each screw.											
6	Make sure the billet grille is centered and tighten the fasteners.											
7	Reinstall the black plastic cover which was removed in step 2.											
8	Installation completed!!!											

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!