

Grille Installation Instruction

Part#	GR	06GFC10S	Appl	Application 2		2015-2016 Ford F-150 Main Upper			
	ltem	Part Nar	ne	QTY	Description	ltem	Part Name	QTY	Description
Parts Lis	1	Mesh Grille		1	Stainless steel	4	Fender Washers	7	
. unto Ele	2	"Z" Brackets (L	Long) 2			5	Nylon Lock Nuts	12	10-24
	3	"Z" Brackets (S	Short)	3					
Install N	otes: O	verlay ×	Rep	lacem	ent 🗸 I	$$ Drill \times Cut \times			
Step		Descrip	otion			illustration			
1	Identify list.	the grille & h	ardware	e with	parts	章 			
2	Turn off	engine and chalk	tires wi	th stop	block . Open Hoc	od.			
3	Identify & locate (10) plastic clips on top of plastic shroud and also (1) additional on each side located at the top of the headlight body panel cover. Carefully pry off to remove and then set aside for reinstallation later.								
4	Remove plastic shroud and then set aside for reinstallation later.								
		ou will need to		el well			s. The headlight plastic boo move completely. The plast		
5		FIG 4				FIG	end the billet grille bars or ta		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little billet of adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!



Part#		GR06GFC10S	Application	2015-2016	Ford F-150 Main Upper		
6	On each side of the factory grille near the bottom corner just outside and behind, there is (1) 8mm bolt, (1) 8mm bolt on each side. Use 8mm socket to remove the (2) bolts.						
7	Or	top of the core supp	oort, remove (4) 8	mm bolts.			
8	Re	move (4) plastic clip	s on upper corne	r near head lam	р.		
	I	FIG 7					
9	loc	cated next to the hor ated at the top ce istic cable support cl	nter of grille. No				
10	The OEM Factory Grille should now be free and ready to remove. Carefully place the grille on a soft cushioned surface and prepare to remove the shutter component which is currently fastened to the backside of the factory grille.						
11	ou	move the (7) 10mm tside edge and the (nter structure.			FIG 10		
12	Re	move the (4) plastic	clips located on t	he top lip.			
13		t factory grille aside ille.	and prepare to in	stall your new	FIG 11		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!



Part#	GR06GFC10S	Application	2015-2016 Ford F-150 Main Upper		
14	Set all extension brac	kets in place sta	n on a flat cushioned surface. arting with large bracket on the lower bottom corners and the smal on them with 10mm nuts.		
15			e with factory hardware that was preciously removed.		
16	Flip up and stand the component to new Grill		up to access top. Re-insert plastic clips which will than secure shutte		
17	Grille assembly is now ready to reinstall on vehicle. Match it up to factory mounting points and reinstall in the reverse order that the grille was removed. Start with the (4) 10mm factory bolts on top and the (2) 8mm bolts located near the bottom corners.				
18	Plug the (2) sensor cor component sensor unit		to the shutter		
19	Place plastic radiator sl making sure the cold ai of the shroud. Align the the (10) plastic clips to	r intake lip is ove factory mounting	pholes and use		

to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!



Part#		GR06GFC10S Application		2015-2016 Ford F-150 Main Upper			
20	wit ins	Carefully put back into place the headlight plastic body panel around the head lamp area making sure to align with 8 tab fasteners and then firmly press into place. Use the (2) bolts to mount and secure the panel on the inside wheel well lip. on each side of the grille at the top corners, reinsert the plastic tabs. (1) on each side					
21	Reinstall the plastic shroud with the fasteners removed in Step 2.			eners removed	N/A		
22	Installation completed!!!				N/A		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!