

Grille Installation Instruction

Rev. 131001

Part# GR07LEG03H Application 1999-2000 GMC Sierra 1500 With Logo Show Main Upper Item **Part Name QTY Description Item Part Name QTY** Description **Parts List** 1 Mesh Grille 2 Stainless steel 4 Lock Nut 10 10-24 2 10-24× 2 1/2" Stud 10 5 Flat Tab A 4 washer 10 6 Flat Tab B 2 × Drill Install Notes: Overlay Replacement Cut Description illustration Step 1 Identify the grille & hardware with parts list. N/A Pop hood, remove the black plastic cover (on top 2 of OEM grille / front panel) from vehicle. This will N/A allow access to the rear of the grille shell. 10--10-24×2 1/2" Studs Secure the stud to the threaded holes on the rear 3 of the grille. 4 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. 4-Flat Tabs A and 8-Lock Nuts and 8-Washers Secure grille using the flat tabs and lock nuts and washers from the back side of the OEM grille 5 shell. 2-Flat Tabs B and 2-Lock Nuts and 2-Washers 6 Make sure the grille is centered and tighten the fasteners. 7 Reinstall the black plastic cover which was removed in step 2. 8 Installation completed!!!

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation

We are not responsible for any damage caused by the installation. Thank you for choosing our product!