

PATENT PRODUCT Grille Installation Instruction

Rev. 181001

	SPECIALIST IN			Crino motanation moti dotton Rev. 181001									
Part#		GR08FFD26C/S/J			Applica	tion		or 2012-2013 Honda Fit Sport Model With Logo Show ain Upper					
		Item	Part Name		QTY	De	scrip	tion	Item	Part Name	QTY	Description	
Parts Li	ist	1	Billet Grille		2 Sta		Stainless steel		3	Screws	4	6-32 X 1.5"	
		2	Toggle Nuts		4	6#	!						
Install Notes: Overlay Replacement													
Step	Description						illustration						
1	Identify the grille & hardware with parts list.												
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.												
3	Center the grille into the opening of the factory grille shell. Be sure the screws are through the OEM grille shell.												
4	Secure the grille using the toggle nuts from the back side of the OEM grille shell.												
5	Make sure the grille is centered and tighten the fasteners.												
6	Reinstall the black plastic cover which was removed in step 2.												
7	Installation completed!!!										Name of the second seco		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!