

## PATENT PRODUCT

Grille Installation Instruction

Rev. 190601

Part#	<i>‡</i>	GR08FGA04 C/S/J		Application		For 2003-2005 Honda Accord Sedan					
		Item	Part Name	QTY	De	scription	Item	Part Name	QTY	Description	
Part	s	1	Billet Grille	1	1 Stainless steel		4	Truss Head Screws	2	6-32×2″	
List	t	2	Washers	2	2 2		5	Nylon Lock Nuts	2	6#	
		3	'J' Hooks	2							
Instal	l No	tes: (	Overlay $\sqrt{}$	Rep	lacen	nent ×	Drill	$oxed{ imes}$ Cut $oxed{ imes}$			
Step	Description						illustration				
1	Identify the grille & hardware with parts list.										
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.										
3	Place a machine screw in each mount on the billet insert. Install a "J" hook from the back with a Nylon lock nut and washer. Place the billet insert in the bumper opening.										
4	Tiah	ton the	puto dovo vit	o the "I"	<b>S</b>		<u>1</u> @	of the human areas Paret	ovor tight		
5			e nuts down with	n the "J"	hooks	catching the r	ear edge	of the bumper cover. Do not	over tighte	en.	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!!