

Grille Installation Instruction

Talt# ON0000A141/11 Application Tol 2000-2000 Holida Nidgelille		Part#	GR08GGA14T/H	Application	For 2005-2008 Honda Ridgeline
---	--	-------	--------------	-------------	-------------------------------

ιαιιπ		0/10	7000A1+1/11			Application		Tor 2000-2000 Florida Magelline					
		Item	Part Name		QTY	Description			Item	Part Name	QTY	Description	
Parts L	ict	1	Mesh Grille		1	Stainless steel			4	Lock Nut	4	6-32	
raits L	ist	2	Screws		4	6-32×3″			5	Flat Tab	4	1	
		3	Washers		4								
Install Notes: Overlay Replacement													
Step	ep Description illustration												
1	Identify the grille & hardware with parts list.												
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. Remove the grille from the box. Test fit the grille to make sure that it fits in the shell properly. Make sure the grille is centered.												
3													
4	Thread a screw in each nut welded to the grille.												
5	From the rear, place a tab on each screw. Now thread a nut and a washer on each screw.												
6	Make sure the grille is centered and tighten the fasteners.												
7	Reinstall the black plastic cover which was removed in step 2.												
8	Installation completed!!!												

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!