

Rev. 141001

Part#	GR09GFH05T		Application		10-12 Subaru Legacy Main Upper				
	Item	Part Name	e QTY	De	escription	Item	Part Name	QTY	Description
	1	Mesh Grille	1	Sta	inless steel	6	Top Mounting Plate-Right	1	
	2	Keyslot Studs	4	4 #6-32		7	Emblem Mounting Plate	1	
Parts Lis	3	ESNA Half Nuts	12	12 #6-32		8	Top Mounting Plate-Left	1	
	4	Washers	4			9	Lower Grille Tape Location Template	1	
	5	Double Faced T	ape 1			10	Lower Grille Hole Location Template	1	
Install Notes: Overlay × Replacement ✓ Drill × Cut ✓									
Step	Step Description				illustration				
1	Identify the grille & hardware with parts list.								
2	Open the hood and carefully apply several layers of masking tape to the painted grille openings(around the upper factory grille). Remove the six factory push fastener across the top of the factory grille.								
3	Remove the phillips screws that attach the factory grille to the bumper cover.								
4	Use a short phillips screwdriver to remove the lower two retaining screws.								
5	Once the bottom screws have been removed, pull the grille up and out to clear the bumper cover. The lower side alignment tabs may break off during the removal procedure.								
3									
6	Use a flat blade screwdriver and release the lower emblem retaining clip.								
7	Use a heat gun to heat the area behind the emblem to soften the factory double faced tape.								

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



A	AUTO PARTS SPECIALIST INC.	Grille In	stallation Instruction	Rev. 141001	
Part#	GR09GFH05T	Application	10-12 Subaru Legacy Main U <sub>I</sub>	pper	
8		egee to pry the fac	pins protruding from the back of the grille (see potory emblem from the factory grille. Do not use		
9	Remove the factory double faced tape and install the supplied double faced tape(as shown), then remove the double faced tape liner(not shown).				
	Install the supplied emble	m mounting plate	making sure that the holes in the plate fit over t	the short alignment pins on the	
10	back of the factory embler	m. Press firmly to ser grille tape location			
12	Cut out and align the lower center of the hole.	er grille hole location	on template, taping it into place. Use an awl or s	similar pointed tool to mark the	
13	Remove the template and	drill through the m	nark made in the previous step with a 5/16" dril	II bit.	
	111 200 (Control 1074)	2 Swaru Legery en Dobe volv Legeten Temestr 2009 - ID	12		
14			of the slots made in the previous step and scuff nd anything inside the grille opening with flat or		
15	Remove the upper factory	plastic push faste	eners across the top of the factory plastic support	rt panel and remove the panel.	
				$\overline{}$	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Rev. 141001

	OUTO PARTS SPECIALIST INC.	Offine III	Stallation instruction	Rev. 141001
Part#	GR09GFH05T	Application	10-12 Subaru Legacy Main Upper	
		13		4
16	Use a 5/16" drill bit to enl	arge the slots in th	ne bumper cover for stud clearance.	
17	Peel off the protective cov	er from the stainle	ess steel surround at the emblem mounting area.	
		15		
18	Align the emblem assemb	ly over the emblen	n mounting area, making sure the studs pass through	the mounting holes.
19	secure the emblem assen	nbly using the supp	olied washers and nuts.	
20	Alin the upper mesh grille	, making sure the l	lower mounting studs pass through the slots enlarged	in step 15
21	Install a washer and a nut tight against the bumper of		ower four mounting studs and tighten until the lower ed	dge of the mesh grille is
22	Reinstall the factory plasti	c panel removed ir	n step 14.	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.



Rev. 141001

Part#	GR09GFH05T	Application	10-12 Subaru Legacy Main Upper			






23 Install the factory plastic push fasteners to secure the grille top plate to the support.

Peel off the protective masking tape from the bumper cover by pulling it back over itselt to minimize breakage.

Peel off the protective cove from the stainless steel surrounds. Thoroughly clean the grilles to finish the installation.



25

26





CAUTION: Be Careful while cleaning as the edges of the stainless steel can be very sharp.

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.