

PATENT PRODUCT

Grille Installation Instruction

Part#	GR10GFF04T	Application	2009-2010 Jeep Grand Cherokee					
--------------	------------	--------------------	-------------------------------	--	--	--	--	--

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	7	SS. mesh grille	4	Kept Nut	28	#6
	2	Stud	28	#6-32×1 1/2"	5	Washer	28	#6
	3	Tab	28	With two holes				

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
------	-------------	--------------

1	Identify the grille & hardware with parts list.	<p style="text-align: center;">Left ← Face to the vehicle → Right</p>
----------	---	---

2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. Note: if it is hard to reach the rear of the grille to install the mesh grille, remove the front bumper (with OEM grille shell) from the vehicle.	
----------	---	--

3	Thread the studs to the weld nut on the rear of the mesh grilles (4 studs each). And then, center the billet grilles onto the opening of the OEM grille shell from front side.	
----------	--	--

4	Fasten the mesh grilles on the back side of the OEM grille shell with tabs, washes & kept nuts. (One by one, total 7 pcs)	<div style="border: 1px solid black; padding: 2px; width: fit-content; margin: 10px auto;">Tab, Kept nut & washer</div>
----------	---	---

5	Re-install the black plastic cover onto the vehicle, which was removed on step 2. (If present, re-install the front bumper with 7 mesh grilles onto the vehicle first.)	
----------	---	--

6	Installation completed!!!	
----------	---------------------------	--

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!