

Grille Installation Instruction

Part#	G	R110	SEI55T	Ap	oplicatio	on 2014	-2015			ENSA				
		Item Part Name		QTY Descrip		iption	I	tem	Part Name	Q	TY	Description		
Parts Li	ist	1	Mesh Grille		1	Stainless st	eel		3	Lock Nut	-	6	6-32	
		2 Stud			6			4	Flat Tab		6 1	/		
Install Notes: Overlay								Drill	×	Cut	×			
Step	Description							illustration						
1	Identify the grille & hardware with parts list.													
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.													
3	Secure the stud to the threaded holes on the rear of the grille.							A.	the loss	66-32	2×2"	Stuc	st A	
4	Center the grille into the opening of the factory grille shell.Be sure the studs are through the OEM grille shell.													
5					abs and l rille shell	ock nuts fror	n	6-Flat Tabs and 6-Lock Nuts						
6	Make sure the grille is centered and tighten the fasteners.						N/A							
7	Deinstall the black plactic sever which was							N/A						
8	Inst	allation	complete	ed!!!										

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!

View other car and truck custom grilles made by APG on our website.