 the rear of the grille shell. 3 Secure the stud to the threaded holes on the rear of the grille. 	Grille Installation Instruction Rev. 190401												
Parts List 1 Mesh Grille 1 Stainless steel 4 Lock Nut 5 6-32 2 Flat Tab 3 5 stud 3 6-32×11/2" Install Notes: Overlay N Replacement × Drill Cut × Step Description illustration illustration 1 Identify the grille & hardware with parts list. illustration illustration 2 You may need to remove the black plastic cover (at the bottom of OEM front bumper) from vehicle. This will allow access the rear of the grille shell. 3 3 Secure the stud to the threaded holes on the rear of the grille. 4 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. In the botton the stud, you need mark and drill one holes. 5 Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. 2.1-Tabs and 2-Lock Nuts 5 Secure the grille is centered and tighten the fasteners. 3.Flat Tabs and 3-Lock Nuts 6 Make sure the grille is centered and tighten the fasteners. 7 7 Reinstall the black plastic cover which was removed in step 2. 3.Flat Tabs and 3-Lock Nuts	Part#	GR13GEI68T/H Application					For 2014-2016 Mazda 6						
Parts List 2 Flat Tab 3 5 stud 3 6-32×11/2" Install Notes: Overlay V Replacement × Drill V Cut × Step Description illustration 1 Identify the grille & hardware with parts list. illustration 2 You may need to remove the black plastic cover (at the bottom of OEM front bumper) from vehicle. This will allow access the rear of the grille shell. 3 Secure the stud to the threaded holes on the rear of the grille. 4 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. In the bottor the stud, you need mark and drill one holes. 5 Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. 5 Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. 6 Make sure the grille is centered and tighten the fasteners. 7 Reinstall the black plastic cover which was removed in step 2.			Item	Part Name	QTY	Dese	cripti	on	ltem	Part Name	QTY	Description	
2 Flat Tab 3 5 stud 3 6-32 × 11/2" Install Notes: Overlay N Replacement × Drill V Cut × Step Description illustration 1 Identify the grille & hardware with parts list. Illustration 2 You may need to remove the black plastic cover (at the bottom of OEM front bumper) from vehicle. This will allow access the rear of the grille shell. 3 Secure the stud to the threaded holes on the rear of the grille. 4 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. In the bottor the stud you need mark and drill one holes. 5 Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. 6 Make sure the grille is centered and tighten the fasteners. 7 Reinstall the black plastic cover which was removed in step 2.	Dorto I	ict	1 Mesh Grille 1 Stainless stee		steel		4	Lock Nut	5	6-32			
Install Notes: Overlay Image: Content of the conten of the content of the conten of the content	Fails L	.151	2 Flat Tab 3					5	stud	3	6-32×1 1/2″		
Step Description illustration 1 Identify the grille & hardware with parts list. illustration 2 You may need to remove the black plastic cover (at the bottom of OEM front bumper) from vehicle. This will allow access the rear of the grille shell. 3 Secure the stud to the threaded holes on the rear of the grille. 4 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. In the bottor the stud, you need mark and drill one holes. 5 Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. 5 Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. 6 Make sure the grille is centered and tighten the fasteners. 7 Reinstall the black plastic cover which was removed in step 2.			3	J-Tabs	2				6	stud	2	6-32×2 1/2″	
1 Identify the grille & hardware with parts list. 2 You may need to remove the black plastic cover (at the bottom of OEM front bumper) from vehicle. This will allow access the rear of the grille shell. 3 Secure the stud to the threaded holes on the rear of the grille. 4 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. In the bottom the stud, you need mark and drill one holes. 5 Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. 6 Make sure the grille is centered and tighten the fasteners. 7 Reinstall the black plastic cover which was removed in step 2.	Install I	Note	es: Ov	verlay 🗸	Repla	cement	×	Dri	√	Cut	×		
2 You may need to remove the black plastic cover (at the bottom of OEM front bumper) from vehicle. This will allow access the rear of the grille shell. 3 Secure the stud to the threaded holes on the rear of the grille. 4 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. In the bottom the stud, you need mark and drill one holes. 5 Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. 5 Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. 6 Make sure the grille is centered and tighten the fasteners. 7 Reinstall the black plastic cover which was removed in step 2.	Step	p Description						illustration					
 the rear of the grille shell. Secure the stud to the threaded holes on the rear of the grille. Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. In the botton the stud, you need mark and drill one holes. Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. Make sure the grille is centered and tighten the fasteners. Reinstall the black plastic cover which was removed in step 2. 	1	Identify the grille & hardware with parts list.											
4 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. In the bottom the stud, you need mark and drill one holes. 5 Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. 5 Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. 6 Make sure the grille is centered and tighten the fasteners. 7 Reinstall the black plastic cover which was removed in step 2.	2	You may need to remove the black plastic cover (at the bottom of OEM front bumper) from vehicle. This will allow access to the rear of the grille shell.											
 the stud ,you need mark and drill one holes. Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. Make sure the grille is centered and tighten the fasteners. Reinstall the black plastic cover which was removed in step 2. 	3	Secure the stud to the threaded holes on the rear of the grille.											
 Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell. Wou need mark and drill one holes. Generation of the secure of the prille is centered and tighten the fasteners. Reinstall the black plastic cover which was removed in step 2. 	4	Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. In the bottom of the stud ,you need mark and drill one holes.											
7 Reinstall the black plastic cover which was removed in step 2.	5	Sec	Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell.										
	6	Ма	Make sure the grille is centered and tighten the fasteners.										
8 Installation completed!!!	7	Rei	Reinstall the black plastic cover which was removed in step 2.										
	8	Installation completed!!!											

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!