

PATENT PRODUCT Grille Installation Instruction

Rev. 190301

Part#	GR14FFC98 C/S/J			Application			For 2015-2018 Nissan Maxima with logo show Main Upper + Lower Bumper					
		Item	Part Name		QTY	Description		Item	Part Name	QTY	Description	
Parts Li	ict	1	Billet Grille		5	Stainless steel		4	Tabs	4		
Faits Li	iSt	2	Bolt		6	6-32 ×1	1.5"	5	Screws	4	8# x1"	
		3	Toggle Nut		6	6#						
Install Notes: Overlay $\sqrt{}$ Replacement \times Drill $\sqrt{}$								√ Cut	×			
Step	Descri				ption			illustration				
1	Identify the grille & hardware with parts list. Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille /											
2	front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.											
3	Hold the grille against the OEM grille shell, center and mark holes for drilling. Remove grille and drill holes according to your mark.											
4	Secure both side billet grille using the screws and tabs from the back side of the OEM grille shell. Secure upper and lower billet grille using the toggle nuts from the back side of the OEM grille shell. (4) Screws (4) Tabs Mark and drill 4 holes (6) Toggle Nuts (6) Bolts											
5	Mal	Make sure the grille is centered and tighten the fasteners. But not over-tighten.										
6	Rei	Reinstall the black plastic cover which was removed in step 2.										
7	Installation completed!!!											
								V				

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!