



## Grille Installation Instruction

|              |              |                    |                                    |
|--------------|--------------|--------------------|------------------------------------|
| <b>Part#</b> | GR14GEB18T/H | <i>Application</i> | <b>For 2009-2014 Nissan Maxima</b> |
|--------------|--------------|--------------------|------------------------------------|

| Parts List | Item | Part Name   | QTY | Description     | Item | Part Name     | QTY | Description |
|------------|------|-------------|-----|-----------------|------|---------------|-----|-------------|
|            | 1    | Mesh Grille | 1   | Stainless steel | 2    | Push In Clips | 8   |             |

|                       |                                  |   |                                |                              |
|-----------------------|----------------------------------|---|--------------------------------|------------------------------|
| <b>Install Notes:</b> | Overlay <input type="checkbox"/> | Replacement <input checked="" type="checkbox"/> | Drill <input type="checkbox"/> | Cut <input type="checkbox"/> |
|-----------------------|----------------------------------|---|--------------------------------|------------------------------|

| Step | Description   | Illustration |
|------|---|--------------|
| 1    | Identify the grille & hardware with parts list.   | N/A          |
| 2    | Open the hood and remove the factory plastic radiator cover. Remove the factory air intake plate on the driver side of the vehicle . Now remove the factory grille shell; release the molded clips along the perimeter of the grille. | N/A          |
| 3    | Locate the new mesh grille insert. Place the grille into the factory opening. The welded tabs will fit into the factory mounting holes . Place the provided clips into each of the tabs.  | N/A          |
| 4    | Make sure the grille is centered and tighten the fasteners.but do not over-tighten.   | N/A          |
| 5    | Replace the factory air intake plate. Reinstall the radiator cover and all factory clips.   | N/A          |
| 6    | Installation completed!!!   | N/A          |

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.  
 Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.  
 We are not responsible for any damage caused by the installation. Thank you for choosing our product!