

Grille Installation Instruction

Rev. 180901

Part# GR14GED08T/H For 2004-2006 Nissan Maxima 1 PC Cover 2 Holes Application **Part Name QTY Description Item Part Name QTY** Description Item **Parts** List Stainless steel 2 Hair Pin Clips 4 Mesh Grille **Install Notes: Overlay** Replacement Drill Cut Step Description illustration 1 Identify the grille & hardware with parts list. Open the hood and remove the push fasteners retaining the top of the factory grille. Apply masking tape around the factory 2 grille. (Fig 1) To remove the stock grille, you must squeeze the lower retaining clips and pull the grille straight out from the bumper cover. 3 (Fig 2) Slide the grille bottom mounting tabs into the stock mounting brackets. Then insert a hair pin clip into each mounting tab to secure the bottom of the grille. Secure the top of the grille using the push fasteners that were removed in step 2. (Fig 3) Fig 2 Fig 1 Fig 3 Side View 5 Make sure everything is secure and close the hood.

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!

Installation completed!!!

6