

Grille Installation Instruction

Part#	GR14GEF07T			Application		6 Infiniti FX35/ FX45 – Low Bumper Stainless Mesh Grille					
		Item	Part Na	me QTY		Descrip	tion	Item	Part Name	QTY	Description
Parts L	.ist	1	Mesh Grille		1	Stainless ste		4	Nylon Lock Nuts	3	10-24
		2 Studs			3	10-24×2″		5	'J' Hooks	3	
Install Notes: Overlay 🗸 Replacement 🗵							C	Drill ×	Cut ×		
Step	Description						illustration				
1	Identify the grille & hardware with parts list.										
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.						N/A				
3	Test fit the billet in place; the flat aluminum spacer welded to the grille rest on the bottom. Thread the studs into the lower mounting holes. A small amount of liquid thread lock may be applied to the threads. BE SURE NOT TO OVER-TIGHTEN THE STUDS (Over-tightening can cause dimpling to the face of the billets)										
4	Install a J hook and nylon lock nut onto each stud. Center the grille into the opening and wrap the J hooks around the rear of the bumper opening. Tighten the hardware until the grille is held in place.						N/A				
5	Make sure the grille is centered and tighten the fasteners.but do not over-tighten.						N/A				
6	Reinstall the black plastic cover which was removed in step 2.						N/A				
7	Installation completed!!!						N/A				

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!

Looking for dependable car and truck custom grilles? Rely on APG for quality and long-lasting products.