

Grille Installation Instruction

Part#	GR14GFC85T/H Application F						For 2013-2015 Nissan Altima Main Upper						
		Item	Part Name		QTY	Descrip		tion	Item	Part Nam	ne	QTY	Description
Parts L	ict	1	Mesh Grille		1	Stainless S		Steel	4	Studs		10	0.138-32 X 2.5"
Faits L	151	2	Flange Hex	lange Hex Nuts		0.138-32			5	Flat tabs(Lo	ng)	2	
		3	Flat tabs		8								
Install Notes: Overlay \checkmark Replacement \times Drill \checkmark Cut \times													
Step	Description							illustration					
1	Identify the grille & hardware with parts list.												
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.												
3	Thread a stud in each nut welded to the grille. Hold the grille against the OEM grille shell, center and mark holes for drilling. Remove grille and drill holes according to your mark.												
4	Secure the grille using the flat tab and flange hex nut from the back side of the OEM grille shell. (2) 2.5" Studs (2) Flat tabs(Long) (2) Flange Hex Nuts												
5	Ma	ke sure	e the grille is	center	ed and	tighte	n the	fastene	rs. But	not over-tighte	en.		
6	Re	install t	he black pla	stic co	ver whic	h wa	s remo	oved in s	step 2.				
7	Installation completed!!!										K		
(,	The	instruct	ion here is for	VOUR re	eference	only	You m	av need	to bend	the billet grille	bars	or tabs :	a little bit to

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!