

PATENT PRODUCT Grille Installation Instruction

Grille installation instruction															
Part#	GR14HGG74J			Αp	Application		For 2009-2014 Nissan Maxima								
		Item	Part Name		QTY	Y Descrip		tion	Item	Item Part Name		ne	QTY	Description	
Parts L	iot	1	Billet G	rille		2	Stainless ste		teel	4	Push Ir	n Clips		4	
Paris L	ıδι	2	J Hook	S		2				5	J Hooks			2	1 "
		3 U Nuts			4		#8			6	Screws (#6 Head)		4	#8×1 1/4"	
Install N	Notes: Overlay ×			Re	placement V				orill [×	Cut	×			
Step	Description								illustration						
1	Identify the grille & hardware with parts list.														
2	Start from the main upper piece. Open the hood and remove the factory plastic radiator cover. Remove the factory air intake plate on the driver side of the vehicle. Now remove the factory grille shell; release the molded clips along the perimeter of the grille. If installing a bumper insert.														
3	Locate the new grille insert. Place the grille into the factory opening. The welded tabs will fit into the factory mounting holes . Place the provided clips into each of the tabs.														
4	Now move on to the bottom piece. Slide the u-nuts onto J hooks. Insert the screws into the tabs on the billet. Start to thread the shorter J hooks onto the top screws (1). Start to thread the longer J hooks onto the lower screws (2). Center the grille in place. Wrap the hooks around plastic bars in the openings.														
5			the billet removed			tered an	d tighte	en the	fasten	ers, but o	do not ove	er-tighte	en. Rein	stall the b	olack plastic cover
6	Ins	tallation	complete	ed.							_				

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!