Part# GR20LEA72H Application For 2005-2011 Toyota Tacoma Part# Image: Transment of the state of the		Grille Installation Instruction								
1 Mesh Grille 3 Stainless steel 5 Flange Nuts 30 10-24 Parts List 2 L Brackets 9 75° 6 Phillips Screws 13 10°X1/2″ 3 L Brackets 4 70° 7 Threaded rods 4 10°X1/2″ Install Notes: Overlay × Replacement ✓ Drill ✓ Cut ✓ 1 Identify the grille & hardware with parts list. 2 Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. 3 Optional: Using factory instructions, remove the entire front grille shell. Image Nuts provided. 4 Remove the OEM black plastic grille ront ogrille shell cavity. Image Nuts provided. 5 Position the center piece of grille onto grille shell cavity. Image Nuts provided. 6 Secure the stud to the threaded holes on the rear of the grille. Image Nuts provided. 7 Center the grille into the opening	Part#	GR20LEA72H Application For 200				5-2011 Toyota Tacoma				
Parts List 2 L Brackets 9 75 6 Phillips Screws 13 10 ¹ X1/2 ¹ 3 L Brackets 4 70 ¹ 7 Threaded rods 4 10 ¹ X1 1/2 ¹ 4 Metal Brackets 4 20 ¹ 19mm 7 Threaded rods 4 10 ¹ X1 1/2 ¹ Install Notes: Overlay Replacement Image: Display to the provided rods 13 10 ¹ X1 1/2 ¹ 1 Identify the grille & hardware with parts list. Drill Cut V 2 Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. 3 3 Optional: Using factory instructions, remove the entire front grille shell . 4 4 Remove the OEM black plastic grille from the shell. Image: Display to the grille shell . 5 Position the center piece of grille onto grille shell cavity. Image: Display to the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. 8 Backets and holes on the shell brough the tabe of L Brackets and holes on the shell brough the tabe of L Brackets and holes on the shell brough the tabe of L Brackets and holes on the shell brough the tabe of L Brackets and holes on the shell brough the tabe of L B		ltem	Part Name QT		Description		Item	Part Name	QTY	Description
3 L Brackets 4 70° 7 Threaded rods 4 10°X111/2″ 4 Metal Brackets 4 20°19mm 1 1 1 1 1 Vertage X Replacement V Drill V Cut V 1 Identify the grille & hardware with parts list. Vertage		1	1 Mesh Grille		Stainless steel		5	Flange Nuts	30	10-24
4 Metal Brackets 4 20'19mm Install Notes: Overlay × Replacement √ Drill √ Cut √ Step Description illustration 1 Identify the grille & hardware with parts list. Illustration 2 Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. 3 Optional: Using factory instructions, remove the entire front grille shell . 4 Remove the OEM black plastic grille from the shell. 5 Position the center piece of grille onto grille shell. Be sure the studs are through the OEM grille shell. 6 Secure the stud to the threaded holes on the rear of the grille. 7 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. 8 mark locations for drilling on the shell through the holes of the shell scure there with flange nuts provided. 9 Grille, its advised to use locate on stude goring into Grille. Position the let and right pieces of drille onto grille shell. Attach the grille scure there with location for drilling on the shell scure there with location for drilling on the shell struct there grille is not wide logge nuts provided. 9 Grille ins advised to use locate on stude goring into Grille. Po	Parts Li	st 2	L Brackets	9	75°		6	Phillips Screws	13	10 [#] X1/2 <i>"</i>
Install Notes: Overlay × Replacement ✓ Drill ✓ Cut ✓ Step Description illustration 1 Identify the grille & hardware with parts list. Identify the grille & hardware with parts list. Identify the grille & hardware with parts list. 2 Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. 3 Optional: Using factory instructions, remove the entire front grille shell . 4 Remove the OEM black plastic grille from the shell. 5 Position the center piece of grille onto grille shell cavity. Image: Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. 6 Secure the stud to the threaded holes on the rear of the grille. 7 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. 8 Mark locations for drilling on the shell through the tobs of L Brackets. Then drill holes on the shell shear of L Brackets and holes on the shell shear of L Brackets and holes on the shell shear of L Brackets and holes on the shell shear of L Brackets and holes on the shell. 9 Grille, his advised to use of the dright pieces of Grille, not advised to use the grille pose of grille pose of L Brackets and holes on the shell. Attach the two pieces grills to th		3	L Brackets	4	70°		7	Threaded rods	4	10 [#] X1 1/2″
Step Description illustration 1 Identify the grille & hardware with parts list. Identify the grille & hardware with parts list. 2 Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. 3 Optional: Using factory instructions, remove the entire front grille shell . 4 Remove the OEM black plastic grille from the shell. 5 Position the center piece of grille onto grille shell cavity. 6 Secure the stud to the threaded holes on the rear of the grille. 7 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. 8 Mark locations for drilling on the shell through the lose of L Brackets. Then drill holes on the shell by inserting the screws through the tabs of L. 8 Inscript a drive of to use locate on studg going into faile. Position the let and right pieces of Grille, its advised to use locate on studg going into faile. Position the let and right pieces of Grille not grille shell. Attach the two pieces grille to the shell with metal brackets and flange nuts provided. 9 Grille onto grille is centered and tighten the fasteners. 10 Make sure the grille is centered and tighten the fasteners.		4	Metal Brad	ckets 4	20*19mm					
1 Identify the grille & hardware with parts list. 2 Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. 3 Optional: Using factory instructions, remove the entire front grille shell . 4 Remove the OEM black plastic grille from the shell. 5 Position the center piece of grille onto grille shell cavity. 6 Secure the stud to the threaded holes on the rear of the grille. 7 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. 8 Mark locations for drilling on the shell through the holes of the shell secure them with flange nuts provided. 8 Attach threaded stud to left and right pieces of Grille, its advised to use locate on studs going into Grille, its advised to use locate on studs going into Grille, provided. 9 Grille onto grille shell. Attach the wo pieces grille to the shell shackets and flange nuts provided. 10 Make sure the grille is centered and tighten the fasteners.	Install N	lotes: C	s: Overlay 🛛 Repla		icement $$	cement 🗸 Dri		Cut √		
2 Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. 3 Optional: Using factory instructions, remove the entire front grille shell . 4 Remove the OEM black plastic grille from the shell. 5 Position the center piece of grille onto grille shell cavity. 6 Secure the stud to the threaded holes on the rear of the grille. 7 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. 8 Mark locations for drilling on the shell hous on the sole of using the screws through the shell. Secure them with flange nuts provided. 9 Attach threaded stud to left and right pieces of Grille. Position the left and right pieces of Grille not grille shell. Attach the two pieces of Grille not grille shell. Attach the two pieces of Grille onto grille shell. Attach the two pieces of Grille onto grille shell. Attach the two pieces of Grille onto grille shell. Attach the two pieces of Grille not grille shell. Attach the two pieces of Grille onto grille shell. Attach the two pieces of Grille onto grille shell. Attach the two pieces of Grille onto grille shell. Attach the two pieces of Grille onto grille shell cavity. Mark locations for drilling on the shell. Attach the two pieces of Grille onto grille shell. Attach the two pieces of Grille onto grille shell. Attach the two pieces of Grille onto grille shell. Attach the two pieces of Grille onto grille shell. Attach the two pieces of Grille onto grille shell. Attach the two pieces of Grille onto grille shell. Attach the two pieces of Grille onto grille shell. At	Step	p Description illustration								
3 Optional: Using factory instructions, remove the entire front grille shell . 4 Remove the OEM black plastic grille from the shell. 5 Position the center piece of grille onto grille shell cavity. 6 Secure the stud to the threaded holes on the rear of the grille. 7 Center the grille into the opening of the factory grille shell. Be sure the studs are through the holes of L Brackets. Then drill holes on those locations. Attach the grille to the shell by inserting the screws through the tabs of L Brackets and holes on the shell, secure them with flange nuts provided. 8 Attach threaded stud to left and right pieces of Grille is shell. Cavity. Mark locations for drilling on the shell, secure them with flange nuts provided. 9 Attach threaded stud to left and right pieces of Grille onto grille shell. Cavity. Mark locations for drilling on the shell approximation of the shell secure stude to the shell by inserting the screws through the tabs of L Brackets and holes on the shell, secure them with flange nuts provided. 10 Make sure the grille is centered and tighten the fasteners.										
4 Remove the OEM black plastic grille from the shell. 5 Position the center piece of grille onto grille shell cavity. 6 Secure the stud to the threaded holes on the rear of the grille. 7 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. 8 Mark locations for drilling on the shell through the holes of L Brackets. Then drill holes on those locations. Attach the grille to the shell by inserting the screws through the tabs of L Brackets and holes on the shell, secure them with flange nuts provided. 9 Attach threaded stud to left and right pieces of Grille. Its advised to use locations for dright pieces of Grille. Nestion the left and right pieces of Grille onto grille shell. Attach the two pieces grille to the shell with metal brackets and flange nuts provided. 10 Make sure the grille is centered and tighten the fasteners.		the grille shell.								
5 Position the center piece of grille onto grille shell cavity. 6 Secure the stud to the threaded holes on the rear of the grille. 7 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. 8 Mark locations for drilling on the shell through the holes of L Brackets. Then drill holes on those locations. Attach the grille to the shell by inserting the screws through the tabs of L Brackets and holes on the shell, secure them with flange nuts provided. 8 Attach threaded stud to left and right pieces of Grille. Position the left and right pieces of Grille onto grille shell. Attach the two pieces grille to the shell with metal brackets and flange nuts provided. 9 Grille noto grille shell. Attach the two pieces grille to the shell may be also and the shell. Attach the two pieces grille to the shell with metal brackets and flange nuts provided. 10 Make sure the grille is centered and tighten the fasteners.	3	Optional: Using factory instructions, remove the entire front grille shell .								
 6 Secure the stud to the threaded holes on the rear of the grille. 7 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. 8 Mark locations for drilling on the shell through the holes of L Brackets. Then drill holes on those locations. Attach the grille to the shell by inserting the screws through the tabs of L Brackets and holes on the shell, secure them with flange nuts provided. 8 Attach threaded stud to left and right pieces of Grille, its advised to use locate on studs going into Grille. Position the left and right pieces of Grille onto grille shell cavity. Mark locations for drilling on the shell with metal brackets and flange nuts provided. 10 Make sure the grille is centered and tighten the fasteners. 	4	Remove the OEM black plastic grille from the shell.								
 Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. Mark locations for drilling on the shell through the holes of L Brackets. Then drill holes on those locations. Attach the grille to the shell by inserting the screws through the tabs of L Brackets and holes on the shell, secure them with flange nuts provided. Attach threaded stud to left and right pieces of Grille. Position the left and right pieces of Grille onto grille shell cavity. Mark locations for drilling on the shell. Attach the two pieces grille to the shell with metal brackets and flange nuts provided. Make sure the grille is centered and tighten the fasteners. 	5	Position the center piece of grille onto grille shell cavity.								
 Mark locations for drilling on the shell through the holes of L Brackets. Then drill holes on those locations. Attach the grille to the shell by inserting the screws through the tabs of L Brackets and holes on the shell, secure them with flange nuts provided. Attach threaded stud to left and right pieces of Grille. Position the left and right pieces of Grille onto grille shell cavity. Mark locations for drilling on the shell. Attach the two pieces grille to the shell with metal brackets and flange nuts provided. Mark locations for drille is centered and tighten the fasteners. 	6	Secure the stud to the threaded holes on the rear of the grille.								
 the holes of L Brackets. Then drill holes on those locations. Attach the grille to the shell by inserting the screws through the tabs of L Brackets and holes on the shell, secure them with flange nuts provided. Attach threaded stud to left and right pieces of Grille, its advised to use locate on studs going into Grille. Position the left and right pieces of Grille onto grille shell cavity .Mark locations for drilling on the shell. Attach the two pieces grille to the shell with metal brackets and flange nuts provided. Make sure the grille is centered and tighten the fasteners. 	7	Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.								
 Grille, its advised to use locate on studs going into Grille. Position the left and right pieces of Grille onto grille shell cavity .Mark locations for drilling on the shell. Attach the two pieces grille to the shell with metal brackets and flange nuts provided. Make sure the grille is centered and tighten the fasteners. 	8	the holes of L Brackets. Then drill holes on those locations. Attach the grille to the shell by inserting the screws through the tabs of L Brackets and holes on the shell, secure them								
	9	Grille, its advised to use locate on studs going into Grille. Position the left and right pieces of Grille onto grille shell cavity .Mark locations for drilling on the shell. Attach the two pieces grille to the shell with metal brackets and flange nuts								
11 Reinstall the black plastic cover which was removed in step 2, now installation completed!	10	Make su	re the grille is	centered and	tighten the fas	teners.				
	11	Reinstall	the black pla	stic cover whi	ch was remove	d in step 2	, now ins	tallation completed!		

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!

Looking for dependable car and truck custom grilles? Rely on APG for quality and long-lasting products.