


### **INSTALLATION INSTRUCTIONS**

3" SIDEBARS ROCKER PANEL MOUNT 2014 1500 SILVERADO/SIERRA DOUBLE CAB 07-13 1500 SILVERADO/SIERRA EXTENDED CAB 07-14 25-3500 SILVERADO/SIERRA EXTENDED CAB EXCLUDES DIESEL W/DEF PART#204046-2 / 204046

5" OVAL BENT END SIDEBARS ROCKER PANEL MOUNT 2014 1500 SILVERADO/SIERRA DOUBLE CAB 07-13 1500 SILVERADO/SIERRA EXTENDED CAB 07-14 25-3500 SILVERADO/SIERRA EXTENDED CAB EXCLUDES DIESEL W/DEF

#### PARTS LIST:

Qty	Description	Qty	Description
1	Driver side tube assembly	12	M8-1.25 Clip-On Nuts
1	Passenger side tube assembly	24	M8-1.25 x 25mm Hex Bolt
6	3" sidebar bracket	24	8mm lock washer
		24	8mm x 24mm x 2mm flat washer



#### **PROCEDURE:**

## REMOVE CONTENTS FROM BOX. VERIFY ALL PARTS ARE PRESENT. READ INSTALLATION INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION.

1. Start the installation under the driver side of the vehicle. Locate the 1st, 2nd and 4th mounting tabs along the bottom edge of the body, (Figure 1). If necessary, hold the driver side Sidebar up in place to help determine the correct mounting holes to use along the bottom of the body.

Vehicles with flat tab, no threaded hole: Select (1) 8mm Clip Nut. Slide the Clip Nut over the first tab with the nut facing up behind the tab, (Figure 1). Line up threaded nut with hole in tab. Vehicles with factory installed threaded insert in tab: Thread hex bolt into threaded insert from the backside-down to clear paint as required.

 Locate the inner mounting location on the back of the rocker panel directly above the flat tab in Step 1. Vehicles without threaded hole: Remove the rubber plug from the larger hole, (Figure 2). Select (1) 8mm Clip Nut. Slide the Clip Nut into the larger hole. Line up the threaded nut with the smaller hole, (Figure 3).

Vehicles with factory installed threaded insert: Thread 8mm Hex Bolt into threaded insert to clear paint as required. Use a small amount of oil if necessary, (Figure 1).

- Select (1) Mounting Bracket. NOTE: Brackets are universal and will fit left or right side. Bolt the Mounting Bracket to the Clip Nuts and/or the factory threaded holes with (2) 8mm Hex Bolts, (2) 8mm Lock Washers and (2) 8mm Flat Washers, (Figure 4). Snug but do not fully tighten the hardware.
- 4. Repeat Steps 1 3 for all Bracket installations.
- 5. Carefully position the Driver Sidebar onto the (3) Mounting Brackets. Attach the Sidebar to the Mounting Brackets with (6) 8mm x 25mm Hex Bolts, (6) 8mm Lock Washers and (6) 8mm Flat Washers, (Figures 4). Do not tighten hardware at this time.
- 6. Level and adjust the Sidebar and tighten all hardware.
- 7. Repeat Steps 2 6 for passenger Sidebar installation.
- 8. Do periodic inspections to the installation to make sure that all hardware is secure and tight.

**To protect your investment**, wax this product after installing. Regular waxing is recommended to add a protective layer over the finish. Do not use any type of polish or wax that may contain abrasives that could damage the finish. **For stainless steel**: Aluminum polish may be used to polish small scratches and scuffs on the finish. Mild soap may be used also to clean the Sidebar.

For gloss black finishes: Mild soap may be used to clean the Sidebar.

5" OVAL BENT END SIDEBARS ROCKER PANEL MOUNT 2014 1500 SILVERADO/SIERRA DOUBLE CAB 07-13 1500 SILVERADO/SIERRA EXTENDED CAB 07-14 25-3500 SILVERADO/SIERRA EXTENDED CAB EXCLUDES DIESEL W/DEF

# **Driver Side Installation Pictured** Factory 8mm threaded insert in body panel Use 8mm Clip Nut or factory threaded insert if equipped **Remove plug** (Fig 1) Example of mounting location with factory threaded hole (2) 8mm Clip Nuts (Fig 2) Example of mounting location without factory threaded hole in rocker panel (2) 8mm x 25mm Hex Bolts (2) 8mm Lock Washers (2) 8mm Flat Washers (Fig 3) Insert 8mm Clip Nut as required (2) 8mm x 25mm Hex Bolts (2) 8mm Lock Washers (2) 8mm Flat Washers Fig 4

Learn more about other off-road bumpers by Aries on our website.