



Model: **78935**

Product Type:

**UNIVERSAL FUEL TANK LOCK WRENCH**



**WARNING**



Study, understand and follow all instructions provided with this product. Read these instructions carefully before installing, operating, servicing or repairing this tool. Keep these instructions in a safe accessible place.

**INTENDED USE OF THE TOOL**

The 78935 Universal Fuel Tank Lock Wrench is designed to remove 2004+ 7" size fuel tank lock rings for fuel senders. Do not use this tool outside of the designed intent. Never modify the tool for any other purpose or use.



**WARNING**



**Caution: To help prevent personal injury**

- Use of this product can expose you to chemicals including ethylene glycol, gasoline vapors and engine exhaust, which are known to the State of California to cause cancer, birth defects, or reproductive harm. Always wear ANSI approved safety equipment, safety glasses and clothing when using this product. Study, understand, and follow all instructions provided with this product. Failure to read and follow all warnings and operating instructions may result in damages and serious injury or death.
- Always wear ANSI approved goggles when using this product. (Users and Bystanders).
- Never use this tool for any application other than for which it was designed.
- Only use accessories designed for this tool.
- Never alter or modify this tool in any way.
- Improper operation and/or maintenance of the tool, modification of the tool, or use of the tool with accessories not designed for it could result in serious injury or death.
- Always select the correct accessories of the correct size and design for the job that you are attempting to perform.
- Always work in a clean, safe, well-lit, organized and adequately equipped area.
- Do not begin repairs without assurance that vehicle is in secure position, and will not move during repair.



**Astro Pneumatic  
Tool Company**

**PRODUCT INFORMATION:**

- Needed to remove fuel tank locking rings on fuel senders for many 2004 and newer vehicles
- Applications include GM/Chrysler/Dodge, Ford, BMW, Hyundai, Jaguar, Mercedes, Nissan, Subaru, Saab, Volvo and more
- 7" size, 1/2" drive for use with ratchet or breaker bar

**INSTRUCTIONS:**

- 1) Spray fuel tank locking ring assembly with penetrant like WD-40 and let it soak for 20-30mins.
- 2) Clip the feet of the wrench into the tabs of the locking ring
- 3) Press down on the wrench and turn your ratchet or breaker bar counter clockwise
- 4) When installing, move wrench to new location on the lock ring so as to not cause any bends on ring from repeated use

**POPULAR APPLICATIONS FOR THIS TOOL**

Model year 2004+, list does not include all applications

BMW

Chrysler/Dodge: Mini vans, PT Cruiser, Dakota, Durango, Charger, Magnum, Jeep Compass (and more Jeep)

Ford: F-150 (and more trucks), Explorer, Escape

GM: 1/2-ton and 3/4-ton trucks, Suburban, Malibu.

Hyundai: Santa Fe (and more Hyundai)

Jaguar

Mercedes: (all w/ "bayonet type cap") platform #'s 222, 213, 242, 205, 253, 218, 217, 212, 204, 447, 924

Mercury

Nissan: Pathfinder, Sentra (and more Nissan)

Saab: 03-11 9-5, 9-3

Volvo

**SPECIFICATIONS:**

7" span, 3 point engagement

**UNIVERSAL FUEL TANK LOCK WRENCH**



**DO NOT DISCARD – GIVE TO USER**

Discover other fuel system service on our website.