



7848-01 - Spring Compressor

For use on 5/8" diameter retainer springs found on most newer vehicles. Industrial finish. 6.29" Length



7848-02 - Brake Spring Installer

Installs brake springs on 1979 and later GM brakes on X, J, A and N body styles. Industrial finish. 9.37" Length



7848-03 - Spring Removal Tool

For use on 5/8" diameter retainer springs found on most new vehicles. Industrial finish. 6.1" Length




7848-04 - Brake Retaining Spring Tool

For removing brake springs on full-size cars and pick-ups with drum style brakes. Industrial finish. 9.37" Length



7848-05 - Brake Spring Pliers

Designed by professional mechanics to remove and replace springs, this narrow point with "Straight-in-line" pull on spring design includes special socket for application on all hydraulic brakes. 9.37" Length



7848-06 - Brake Spoon Adjustment

Tool adjusts clearance between drum brake and brake shoe. It fits through a slot in the backing plate and turns the star wheel. Ends of tool are offset for hard-to-reach areas on small cars.



7848-07 - Brake Spoon Adjustment

Tool adjusts clearance between drum brake and brake shoe. It fits through a slot in the backing plate and turns the star wheel. Ends of tool are offset for hard-to-reach areas on small cars.



7848-08 - Brake Spoon Adjustment

Adjusts clearance between drum brake and brake shoe by fitting tool through a slot in the backing plate and turns the star wheel. Tool is designed to clear the axle housing to reach the slot on top of the backing plate on some trucks.