



INSTALLATION GUIDE

2016+ BMW 340i
Touring Edition Exhaust

2016+ BMW 340i
Performance Mid Pipe

FOR RACING USE ONLY

Congratulations on your purchase of the AWE Tuning Touring Edition Exhaust for the 2016+ BMW B58 engine 340i.

Exquisite build quality and superior performance distinguishes this [exhaust](#) from all others.

PARTS LIST

Touring Edition Exhaust

- 1 Coupler (part TZ)
- 1 Rear 180 Technology™ resonator assembly (part KH)
- 1 Dual outlet rear section (part LX)
- 2 3.00" Accu-Seal clamp
- 2 Hanger collar, 3/8"
- 1 Allen key, 7/64"
- 1 80mm Accu-Seal (#10-0798)
- 2 90mm or 102mm tips
- 2 exhaust tip clamps (only applicable for 102mm tips)

Performance Mid Pipe (compatible only with AWE Tuning Touring Edition Exhaust)

- 1 Front section (part UA)
- 1 Inlet section (part KC)
- 1 Non-resonated mid tube (part LY)
- 4 3.00" Accu-Seal clamps
- 1 Coupler (part KG)

Step 1

If you are installing the AWE Tuning Touring Edition Exhaust *with Performance Mid Pipe*, there is no need to cut the factory exhaust, so skip to Step 3.

If you are installing just the Touring Edition Exhaust and re-using the factory mid pipe, the exhaust will have to be cut *just* before the rear muffler. **See Figure 1.**





Figure 1

Step 2

Locate the factory cut dimple at the rear of the exhaust. Measure from the dimple towards the FRONT of the car 2.25" and mark. Cut the exhaust as clean and straight as possible at the mark you created. **See Figure 2.**

Unclip the wire harness to the valve motor, then remove the nuts securing the exhaust hangers to the chassis. Remove the muffler from the vehicle.


Deburr the ends of the cut tubing and ensure outside of the tube is free of debris.




Step 3

If you are *not* installing the AWE Tuning Performance Mid Pipe, skip to **Step 7**.

Spray penetrating oil on the factory cat section exhaust clamp nut/threads and the 13mm nut for the exhaust support bracket. Let soak, then loosen the clamp and remove the 13mm nut. **See Figure 3.**



Remove chassis brace at the center of the vehicle as seen in **Figure 4**.



Step 4

If the AWE Tuning Touring Edition Exhaust had been previously installed, loosen both of the clamps at the rear coupler and carefully slide the rear muffler assembly out of the clamp and away from the OEM exhaust. See **Figure 5**.

If factory rear muffler is still installed and you are removing the entire exhaust in one piece, support the rear muffler and unclip the wire harness to the valve motor. Remove the nuts securing the exhaust hangers to the chassis.

To remove the exhaust from the vehicle, drop it 8-10" downward from the chassis and pull rearward with a twisting motion to separate the junction at the cat section. Due to the weight of the system, it is recommended that two people perform this step.



Figure 5

Step 5

Installation of the AWE Tuning Performance Mid Pipe is essentially the reverse of removal.

Use the supplied 80mm Accu-Seal clamp to join the front section to the factory cat section. Line up the hole in the AWE exhaust bracket to the stud protruding straight down on the front chassis mount. See **Figure 6**.




Figure 6

Step 6

Install the balance of components using the supplied 3.0" Accu-Seal clamps at arrows in **Figures 7 and 8**.

Leave the clamps loose until the tips on the exhaust system are adjusted into position while simultaneously ensuring clearance at the mid brace.

Use the supplied coupler (KG) with (2) 3.0" Accu-Seal clamps, at **Arrow A** in **Figure 8**, to attach the AWE Tuning Performance Mid Pipe to the AWE Tuning Touring Edition Exhaust.




Figure 7




Figure 8

Step 7

Pre-assemble tip outlet section, at arrow in **Figure 9**, onto the rear 180 Technology™ resonator assembly outlet using supplied 3.0" Accu-Seal clamp.

Slip on factory hanger brackets to the exhaust hanger bars.

Use supplied M8 hardware to secure passenger outlet tab to rear muffler bracket as shown in **Figure 10**.



Use supplied coupler and two 3.0" Accu-Seal clamps to attach factory mid pipe to the muffler inlet. For proper clamping, make sure this coupler equally overlaps the mid pipe outlet and the muffler inlet. Note: for touring rear section only, use the supplied (TZ) coupler with the 3.0" Accu-Seal and 80mm Accu-Seal clamp. The 80mm side of the clamp attaches to the factory cut tubing.

Align tips in valance, tighten all clamps, including the 13mm nut for the chassis support at the front of the exhaust if the AWE Tuning Performance Mid Pipe was installed.

Unbolt valve motor from the factory exhaust.

Use the supplied M6 bolts and washers to mount the valve motor onto the AWE Tuning Touring Edition Exhaust bracket.

Re-connect wire harness to valve motor.



Once installed properly, your AWE Tuning™ Exhaust will provide a lifetime of trouble free performance.

Please note that the rear 180 Technology™ resonator has a small drain hole to allow condensation to escape. Water drops from this area are normal.

Also, please note that the exhaust volume and sound will settle with usage. 800-1000 miles is typically required to fully break in a new exhaust system.

Periodic cleaning of exhaust tips is necessary to maintain proper finish, especially in areas prone to road salt and caustic de-icing solutions. Use a mild soap and water solution or car wax to clean the finish. Avoid using metal polishes, as they can scratch the finish.





Thank you for choosing AWE Tuning as your performance automotive parts supplier. Please remember that a performance car is only as strong as its weakest link. Therefore, it is vital that you maintain your vehicle to factory specifications.

By installing or using the purchased product, the Consumer accepts this warranty and any specific Manufacturer warranties enclosed.

Limited Warranty

The following warranty is valid only in the United States.

The Manufacturer's full warranty applies to all products sold.

Secor Ltd. (AWE Tuning) warrants to the original retail purchaser (Consumer) these products:

2016+ BMW 340i Touring Edition Exhaust
2016+ BMW 340i Touring Edition Exhaust with Performance Mid Pipe

from date of original purchase, against manufacturing defects for:

ONE YEAR on tip finish, LIFETIME on the balance of parts

Upon verification of warranty coverage, AWE Tuning will repair or replace the defective product at their discretion, without charge. This is the only remedy the Consumer has for any loss or damage, however arising, due to nonconformity in or defect of the product. This warranty does not cover consequential damage, loss of time or revenues, labor costs, shipping costs, inconvenience, loss of use of vehicle, damage to the vehicle or components, or other incidental or indirect damage.

All warranties are void if the product was not installed by a certified auto mechanic, improperly serviced, modified, or used in a way not intended by the Manufacturer. Use of product in Motorsports or Racing conditions is grounds for warranty denial. Motorsports and Racing is an inherently abusive operational condition, and it is impossible to warranty for this type of usage.

The Consumer is responsible for ensuring that the product is installed in a safe and proper manner, and should cease usage of the product immediately if an unsafe or improper condition is noted. If an unsafe or improper condition is noted, the Consumer should then immediately contact the facility where the product was installed or AWE Tuning directly.