

AX-NIS325WC-6V

Nissan (with 4.3" display radio) **2010-up**

INTERFACE FEATURES

- Pre-wired ASWC-1 harness (ASWC-1 sold separately)
- Retains the factory backup camera to an aftermarket radio
- Includes the AX-CAM6V 12-volt to 6-volt converter

INTERFACE COMPONENTS

- AX-NIS325WC-6V harness • AX-CAM6V 12-volt to 6-volt converter

APPLICATIONS

NISSAN

Altima <i>coupe</i> 2010-2013*	Juke 2015-up*	Rogue 2014-up
Altima <i>sedan</i> 2010-2012*	Murano 2015-up	Rogue Select 2014-2015*
Altima <i>sedan</i> 2013-up	Quest (without Bose)	Sentra 2010-up*
Cube 2010*	2011-up*	Titan 2013-2015*
Frontier 2013-up*	Rogue 2011-2013*	Versa Note 2014-up*

* For use when retaining the OE backup camera only.

TOOLS REQUIRED

- Wire cutter • Crimping tool • Solder gun • Tape
- Connectors (example: butt connectors, bell caps, etc.)

CAUTION! All accessories, switches, climate controls panels, and especially air bag indicator lights must be connected before cycling the ignition. Also, do not remove the factory radio with the key in the on position, or while the vehicle is running.



Connections to be made

- Connect the **Black** wire to chassis ground, and also to the **Black** wire of the AX-CAM6V.
- Connect the **Red** wire labeled "Camera Power 6V" to the **Blue/Red** wire of the AX-CAM6V.
- Connect the **Green/Purple** wire to the reverse wire of the aftermarket radio, and also to the **Blue/White** wire of the AX-CAM6V.
- Connect the **Yellow** RCA jack to the rear camera input of the aftermarket radio.

12-pin pre-wired ASWC-1 harness:

For the Altima *sedan* 2013-up / Rogue 2014-up only:

This harness is to be used along with the optional ASWC-1 (not included) to retain steering wheel audio controls. Please refer to the ASWC-1 instructions for radio connections and programming.

Note: *Disregard the harness that comes with the ASWC-1.*

- Connect the unlabeled **Red** wire to the accessory wire.