



BACKUPCAM-3

GM Trucks / SUV's 2014-up

INTRODUCTION

The BACKUPCAM-3 is designed to retain the factory backup camera in all but Base model vehicles, so it can be viewed through the display screen on the aftermarket radio.

INTERFACE COMPONENTS

- 12-pin harness with a yellow RCA jack

APPLICATIONS

CHEVROLET

Colorado	2015-up
Silverado1500	2014-up
Silverado 2500/3500	2015-up
Suburban	2015-up
Tahoe	2015-up

GMC

Canyon	2015-up
Sierra 1500	2014-up
Sierra 2500/3500	2015-up
Yukon	2015-up

Note: *This interface will not work in Base model vehicles with a I03 radio.*

Connections to be made


From the 12-pin harness with a Yellow RCA jack

To the aftermarket radio:

- Connect the **Yellow** RCA jack to the BACKUP CAMERA input.

To the vehicle:

- Connect the *female* 12-pin harness with a **Yellow** RCA jack, to the *male* **Gray** harness removed from the Human Machine Interface module. (Figure A)




For the Chevy Colorado and GMC Canyon:

- This module is located in the radio cavity, down low.

For all other models:

- This module is located behind the glove box. There are (2) modules behind the glove box. This module is behind the metal dashboard support. (Figure B)
- Drop the glove box down by first removing the retaining cable on the right side. Then squeeze the glove box sides and gently pull down.
- Remove (6) T-15 Torx screws securing the plastic panel now exposed.



KNOWLEDGE IS POWER
Enhance your installation and fabrication skills by enrolling in the most recognized and respected mobile electronics school in our industry.



Metra recommends MECP
certified technicians

CAUTION! Metra recommends disconnecting the negative battery terminal before beginning any installation, unless the vehicle manufacturer recommends against so. Please check with your local Dealership for more information. All accessories, switches, climate controls panels, and especially air bag indicator lights must be connected before reconnecting the battery or cycling the ignition. Also, do not remove the factory radio with the key in the on position, or the vehicle running. It would be best to remove the key from the ignition and then wait a few seconds before removing the factory radio.