GMRSAV-2



GMRSAV-2

INTRODUCTION

The GMRSAV-2 is designed to provide an audio/video input to the OEM overhead video screen from the aftermarket radio, and provide the audio/video input from the rear seat control panel to the aftermarket radio.

Note: The GMRSAV-2 is designed to work with the overhead video monitors that do not have the DVD player built in.

APPLICATIONS

CADILLAC	
Escalade with NAV	2012-up
CHEVROLET	
Avalanche with NAV	2012-up
Cheyenne with NAV	2012-up
Silverado with NAV	2012-up
Suburban with NAV	2012-up
Tahoe with NAV	2012-up
GMC	
Sierra with NAV	2012-up
Yukon with NAV	2012-up

GMRSAV-2

INTERFACE COMPONENTS

• 16-pin GMLAN RSE harness

TOOLS REQUIRED

- Cutting tool Tape Crimping tool
- Connectors (i.e. butt-connectors, bell caps, etc.)

INSTALLATION INSTRUCTIONS

Important: Before beginning any of the following, disconnect the negative battery terminal to prevent an accidental short circuit.

From the 16-pin harness

- Connect the "To DVD" RCAs to the aftermarket radios audio/video input. Plug **Yellow** in to video-in, **Red** to right audio-in, and **White** to left audio-in.
- Connect the "From DVD" RCAs to the aftermarket radios audio/video output. Plug Yellow in to video-out, Red to right audio-out, and White to left audio-out.
- Connect the loose Black wire to ground.