

Installation Instructions for GMRSAV

GMRSAV GM RSE A/V Harness 2007-up

FEATURES

- Retains the A/V-IN jack (if applicable)
- Provides A/V output to the factory installed rear seat overhead entertainment system *
- Designed for models that have a DVD player built into the factory radio
 - * Only applicable for models with a second row RSE

COMPONENTS

GMRSAV harness

APPLICATIONS

BUICK		GMC	
Enclave	2008-up	Acadia	2007-2016
Cadillac		Acadia Limited	2017
Escalade	2007-2011	Sierra 2500/3500 Δ	2014
Escalade ESV	2007-2011	Sierra (new body) Δ	2007-2013
Escalade EXT	2007-2011	Yukon/Yukon XL ∆	2007-2014
SRX	2007-2009	HUMMER	
CHEVROLET		H2	2008-2009
Avalanche Δ	2007-2013	PONTIAC	
Equinox	2007-2009	Torrent	2007-2009
Silverado 2500/3500 Δ	2014	SATURN	
Silverado (new body) Δ	2007-2013	Outlook	2007-2010
Suburban Δ	2007-2014	OULIOOK	2007-2010
Tahoe Δ	2007-2014	SUZUKI	
Traverse	2009-up	XL-7	2007-2009

△ For 2012-up models with NAV use the GMRSAV-2.

TOOLS REQUIRED

- Wire cutter Crimping tool
- Connectors (example: butt-connectors, bell caps, etc.)

CONNECTIONS TO BE MADE

- Connect the Black wire with a ring terminal to the chassis of the aftermarket radio.
- From the RCA jacks labeled "FROM REAR A/V INPUT" to the A/V input of the aftermarket radio:
 - Connect the Yellow RCA jack to the video in.
 - Connect the Red and White RCA jacks to the audio in.
- From the RCA jacks labeled "TO OVERHEAD SCREEN" to the A/V output of the aftermarket radio:
 - Connect the Yellow RCA jack to the video out.
 - Connect the Red and White RCA jacks to the audio out.

INSTALLING THE HARNESS

 Connect to the GMRSAV harness to the wiring harness in the vehicle located at the radio location.

