




Safety Switch Battery Disconnect


Top Terminal Battery Mount with Accessory Post

Installation

1. Read CAUTION! before installing switch.
2. Remove key from ignition and turn off lights and all accessories.
3. Keep disconnect arm in "open" position until all connections are complete.
4. Remove battery cable from the negative (-) battery post.
5. Clean battery post for a good electrical contact.
6. Install disconnect on the (-) battery post and position as desired.
MAKE SURE THAT YOUR HOOD OR OTHER METAL OBJECTS WILL NOT CONTACT THE SWITCH.
7. Reattach battery cable to the post on the switch.



Try other fine
Battery Doctor® accessories!



#30111 Fuse Block Case



CAUTION!

NOT APPROVED OR INTENDED FOR
MARINE USE.

Read this caution and all instructions thoroughly before installation. Batteries produce explosive gases and can explode! Wear eye protection; keep sparks, flame, cigarettes away from battery. Remember, batteries contain sulfuric acid. Wear safety glasses. In case of contact with skin, eyes, or clothing, flush immediately with large amounts of water and follow through with medical help. Do not use the switch while operating starter, as the battery load may become inductive as well as restrictive, causing an explosion if battery gases are present. Battery disconnects are for use only in well-ventilated environments.

THE USE OF THIS DISCONNECT IS TO CUT BATTERY POWER ON A VEHICLE—AFTER THE VEHICLE'S ENGINE IS TURNED OFF.

WARNING! This product contains chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

Accept no compromises, choose only quality audio connectors and terminals.