

Battery Doctor®

Automotive Battery and Electrical Accessories


Tomorrow's Charging Technology Today

Battery Disconnects

For Side Terminal Batteries

- Mounts on Negative Side Battery Terminal
- Provides 3/8-18 Bolt for Receiving Standard Eyelet Cable Connector
- 3 1/4" W x 3 3/4" L x 1 1/2" H

#20128



For Top Post Batteries

- With 5/8" Diameter Post for Receiving Standard Battery Cable Clamp
- 3" W x 4" L x 2" H

#20138



For Top Post Batteries

- With 5/8" Diameter Post, Plus 5/16-18 Stud and Wing Nut for Extra Connections
- 3" W x 4" L x 2 1/4 1/4" H


#20148



Surface Mounted "In-Line"

- Both Terminals are 5/16" Bolts for Receiving Eyelet Cable Connectors
- 3" W x 4" L x 2" H

#20188



Battery Doctor® Mini Master Battery Disconnect Switches

- For Application Up to 48 Volts
- ISO 8846 Approved
- Continuous Rating: 300 Amps
- Intermittent Rating: 1000 Amps/5 Seconds
- Crank Rating: 700 Amps/10 Seconds
- Can Be Used with 1 or 2 Batteries
- Dimensions: 2 3/4" L x 2 3/4" W x 3" H
- Recess, Flush Top Mount

#20387



#20393



Remote Electric Disconnect Switch

- Switch Manually from Remote Location via Rocker/Toggle Switch
- LED Status Identification for Remote Control Switch
- 9.5VDC - 32VDC
- 275 Amps Continuous
- 455 Amps Intermittent
- 1,250 Amps Cranking
- Power Draw: Switch Off 12mA; Switch On 15mA

NEW!



#20370

