



BESTOP

Highback Front Seat Cover Installation Instructions

For: CJ5 '80-'83, CJ7 '76-'86, Wrangler '86-'91 Part Number: 29227

**DO NOT INSTALL THIS PRODUCT ON ANY VEHICLE OTHER
THAN THOSE LISTED ABOVE.**

Parts List

Seat Cover, Qty - 2

Warning: *DO NOT remove the seats from the vehicle to install this product.*

Seat Covers are not waterproof.

Warning:

This product is designed to enhance the appearance of the vehicle. Do not rely in any way on the components of this product to contain occupants within the vehicle, or to protect against injury or death in the event of an accident. This product will not protect the occupants from falling objects. Never operate vehicle in excess of manufacturer's specifications.

Wear seat belts at all times.

Read and follow, precisely, all installation instructions provided when installing this product. Failure to do so may result in a poor fit and could place occupants of the vehicle in a potentially dangerous situation.

Step One

Orient the Seat Cover with the quilting toward the front of the seat. Slip the opening in the cover over the seat back and pull the cover down to the seat bottom.



Step Two

Locate the flap sewn to the inside of the cover at the corner between the seat back and the seat bottom. Tuck the thick end of the flap as far as possible into the space between the seat back and the seat bottom.

Step Three


Note: On the driver's side seat, make sure that the fabric is tucked behind the seat adjustment lever and that the lever is clear to operate freely.

Fasten Hook and Loop Strips

Slide the cover over the seat bottom and fasten the hook and loop strips at the rear corners to each other. If necessary for a smooth fit, tighten the cord on the bottom of the cover and tuck in any loose fabric.

To Adjust Cord Length


Fasten Hook and Loop Strips



To Fasten Hooks


Slip the two hooks together at right angles to each other.

Turn one hook until they hook to each other.



To secure the hooks, pull them against each other until they click into position.

To Release Hooks: Turn one hook until it is at right angles to the other and pull apart.



Cord length may be adjusted by tying additional knots to pull fabric up tighter

Hook ends together