

B3=====

B3 MATERIAL SAFETY DATA SHEET

B3

B3

B3=====

B3 SECTION 1 - PRODUCT AND COMPANY INFORMATION

B3=====

B3 PRODUCT NAME: POLYAMINOSILOXANE/ POLISHING AGENTS /

B3 ALIPHATIC HYDROCARBONS

B3 COMMON NAME: BESTOP VINYL WINDOW CLEANER 8 OZ. PART# 11203-00

B3 MANUFACTURER'S NAME: BESTOP, INC.

B3

B3

B3

B3=====

B3 SECTION 2 - HAZARDOUS INGREDIENTS

B3 CAS NO. INGREDIENT % BY WT. V.P.

B3 68551-19-9 ALIPHATIC HYDROCARBONS 8 - 10% 0.01mmHg @ 68.0 F

B3 64742-88-7 SOLVENT NAPHTHA 8 - 10% 2.00mmHg @ 68.0 F

B3=====

B3 SECTION 3 - HAZARDS IDENTIFICATION

B3 *****EMERGENCY OVERVIEW*****

B3 * COMBUSTIBLE. CAUSES EYE IRRITATION. WHITE CREAMY SUBSTANCE *

B3 * WITH FRAGRANCE. *

B3 *****

B3 CHRONIC CANCER INFORMATION: NO DATA

B3 TERATOLOGY (BIRTH DEFECT) INFORMATION: NO DATA

B3 REPRODUCTION INFORMATION: NO DATA AVAILABLE

B3=====

B3 SECTION 4 - FIRST AID MEASURES

B3 EYES - MOVE INDIVIDUAL AWAY FROM EXPOSURE AND INTO FRESH AIR.

B3 FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.

B3 SEEK MEDICAL ATTENTION.

B3 SKIN - REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER.

B3 SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.

B3 LAUNDRY CLOTHING BEFORE USE.

B3 INGESTION - DO NOT INDUCE VOMITING. THIS MATERIAL IS AN

B3 ASPIRATION HAZARD. IF INDIVIDUAL IS DROWSY OR

B3 UNCONSCIOUS, PLACE ON LEFT SIDE WITH HEAD DOWN.

B3 SEEK MEDICAL ATTENTION. IF POSSIBLE, DO NOT

B3 LEAVE INDIVIDUAL UNATTENDED.

B3 INHALATION - REMOVE TO FRESH AIR. IF NOT BREATHING GIVE

B3 ARTIFICIAL RESPIRATION. SEEK IMMEDIATE MEDICAL

B3 ATTENTION.

B3=====

B3 SECTION 5 - FIREFIGHTING MEASURES

B3 FLAMMABLE PROPERTIES:

B3 FLASH POINT : 154.0 F METHOD TCC

B3 COMBUSTIBLE. HANDLE AS A COMBUSTIBLE LIQUID

B3 FLAMMABLE LIMITS:

B3 LOWER FLAMMABLE LIMIT: NA

B3 UPPER FLAMMABLE LIMIT: NA

B3 AUTOIGNITION TEMPERATURE: 420.0 F

B3 HAZARDOUS COMBUSTION PRODUCTS: CARBON DIOXIDE, CARBON

B3 MONOXIDE, ALDEHYDES AND VARIOUS HYDROCARBONS.

B3 EXTINGUISHING MEDIA: REGULAR FOAM, CARBON DIOXIDE, AND

B3 DRY CHEMICAL.

B3 FIREFIGHTING INSTRUCTIONS: WATER CAN BE USED TO KEEP

B3 EXPOSED CONTAINERS COOL, TO PROTECT. FIREFIGHTERS SHOULD

B3 WEAR NORMAL PROTECTIVE EQUIPMENT (FULL BUNKER GEAR) AND

B3 POSITIVE-PRESSURE SELF CONTAINED BREATHING APPARATUS.

B3=====

B3 SECTION 6 - ENVIRONMENTAL RELEASE MEASURES

B3 SMALL SPILL: ABSORB SPILL USING VERMICULITE FLOOR ABSORBENT

B3 OR OTHER ABSORBENT MATERIAL.

B3 LARGE SPILL: PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD

B3 BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN UP

B3 HAS BEEN COMPLETED. STOP AT SPILL SOURCE

B3 PREVENT FROM SPREADING. IF RUNOFF OCCURS,

B3 NOTIFY AUTHORITIES AS REQUIRED.

B3=====

B3 SECTION 7 - HANDLING AND STORAGE

B3 HANDLING: CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS

B3 WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN

B3 PRODUCT RESIDUES, ALL HAZARD PRECAUTIONS GIVEN

B3 IN THE DATA SHEET SHOULD BE OBSERVED.

B3 STORAGE: STORE IN WELL VENTILATED AREA. KEEP AWAY FROM

B3 HEAT, SPARKS AND FLAMES. EMPTIED CONTAINERS

B3 MAY RETAIN PRODUCT RESIDUES. PRECAUTIONS APPLY

B3 TO EMPTIED CONTAINERS.

B3

```

B3=====
B3 SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION
B3 ENGINEERING CONTROLS: USE ONLY WITH ADEQUATE VENTILATION.
B3 RESPIRATORY PROTECTION: WHEN RESPIRATORY PROTECTION IS
B3 REQUIRED, OR CONCENTRATIONS ARE UNKNOWN USE
B3 NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR
B3 EQUIPPED WITH ORGANIC VAPOR CARTRIDGES OR
B3 CANISTERS. FOR EMERGENCY AND OTHER CONDITIONS
B3 WHERE EXPOSURE LIMIT MAY BE GREATLY EXCEEDED,
B3 USE AN APPROVED POSITIVE PRESSURE SELF CONTAINED
B3 BREATHING APPARATUS OR POSITIVE PRESSURE AIRLINE
B3 WITH AUXILIARY SELF CONTAINED AIR SUPPLY.
B3 SKIN PROTECTION: FOR BRIEF CONTACT, NO PRECAUTIONS OTHER
B3 THAN CLEAN BODY-COVERING SHOULD BE NEEDED. USE
B3 IMPERVIOUS GLOVES SUCH AS NEOPRENE.
B3 EYE PROTECTION: USE CHEMICAL GOGGLES IN COMPLIANCE WITH
B3 OSHA REGULATIONS.
B3=====
B3 SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES
B3 BOILING POINT: 370.0 - 550.0 F @ 760 mmHg
B3 MELTING POINT: NO DATA
B3 VAPOR PRESSURE: <1.00 mmHg @ 77.0 F
B3 SOLUBILITY IN WATER: LESS THAN 0.01
B3 SPECIFIC GRAVITY: .804 - 0815 @ 60.0 F
B3 pH: NO DATA
B3 ODOR: SWEET
B3 APPEARANCE: WHITE VISCOUS LIQUID
B3=====
B3 SECTION 10 - STABILITY AND REACTIVITY
B3 CHEMICAL STABILITY: STABLE
B3 INCOMPATIBILITY: AVOID CONTACT WITH: CHLORINE,
B3 HYPOCHLORITE, AND STRONG OXIDIZING AGENTS.
B3 HAZARDOUS DECOMPOSITION PRODUCTS: NO DATA
B3 HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
B3=====
B3 SECTION 11 - TOXICOLOGICAL INFORMATION
B3 NO DATA
B3=====
B3 SECTION 12- - ECOLOGICAL INFORMATION
B3 NO DATA
B3=====
B3 SECTION 13 - DISPOSAL CONSIDERATIONS
B3 WASTE MANAGEMENT INFORMATION: DISPOSE OF IN ACCORDANCE
B3 WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.
B3=====
B3 SECTION 14 -TRANSPORT INFORMATION
B3 DOT INFORMATION - 49 CFR 172.101
B3 DOT DESCRIPTION: (FOR GROUND NON BULK SHIPMENTS)
B3 NOT REGULATED
B3 CONTAINER/MODE: NON BULK
B3 NOS COMPONENT: NA
B3 RQ (REPORTABLE QUANTITY) - 49 CFR 172.101
B3 NOT APPLICABLE
B3=====
B3 SECTION 15 - REGULATORY INFORMATION
B3 US FEDERAL REGULATIONS:
B3 TSCA (TOXIC SUBSTANCES CONTROL ACT) STATUS
B3 TSCA (UNITED STATES) THE INTENTIONAL INGREDIENTS OF
B3 THIS PRODUCT ARE LISTED.
B3 CERCLA RQ - 40 CFR 302.4
B3 NONE LISTED
B3 SARA 302 COMPONENTS - 40 CFR 355 APPENDIX A
B3 NONE
B3 SECTION 311/312 HAZARD CLASS - 40 CFR 370.2
B3 IMMEDIATE(X) DELAYED(X) FIRE(X) REACTIVE( ) SUDDEN( )
B3 RELEASE OF PRESSURE
B3 SARA 313 COMPONENTS - 40 CFR 372.65
B3 NONE
B3 STATE AND LOCAL REGULATIONS
B3 CALIFORNIA PROPOSITION 65
B3 NONE
B3=====
B3 SECTION 16 - OTHER INFORMATION
B3 THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO
B3 WARRANTY, EXPRESS OR IMPLIED, IS MADE.

```