TRAILER TONGUE BOX INSTALLATION INSTRUCTIONS

SINGLE, CENTER YOKE TONGUE

- 1. Carefully place the aluminum Trailer Tongue Box in the location where you expect to mount it. Insure the box is centered left to right on the tongue, and the lid will not contact anything when opened. Insure the leveling crank on the trailer (if present) will not hit the box when the crank handle is rotated.
- 2. Locate the two pieces of metal angle that is supplied in the mounting kit.
- 3. Have an assistant hold the box level while you align the angle pieces with the tongue of the trailer and the bottom of the box. Mark the angle locations on the bottom of the box for future mounting locations. (See illustration)
- 4. Locate the self drilling screws included with the mounting kit. Hold the metal angle in place against the bottom of the box and drill through the bottom of the box and into the metal angles.
- 5. Place the box back on the trailer tongue in the original location. Drill through the angles and into the trailer tongue.

NOTE: The screws holding the box to the metal angles should have a sealant applied under the heads to maintain the weather resistant feature of the box. Periodically check the screws for security.

"Y" STYLE TONGUE YOKE

- 1. Carefully place the aluminum Trailer Tongue Box in the location where you expect to mount it. Insure the box is centered left to right on the tongue, and the lid will not contact anything when opened. Insure the leveling crank on the trailer (if present) will not hit the box when the crank handle is rotated.
- 2. If the box lines up with the two sides of the yoke, and the lid will open without interference, use the self drilling screws to attach the box to the trailer frame.
- 3. If necessary for additional stability, use the two pieces of metal angle to attach to the box bottom and trailer frame. If additional stability is not necessary, discard the mounting kit.

NOTE: The screws holding the box to the metal angles should have a sealant applied under the heads to maintain the weather resistant feature of the box. Periodically check the screws for security.

