

BFGOODRICH® LONG TRAIL T/A® TOUR

Tire Size	Service Description	Limited Warranty	Sidewall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width (inches)	Overall Diameter (inches)	Tread Depth (in/32nds)	Rev/Mile @45 mph	Max Load Single (lbs@psi)	UTQG	O.E. Fitments
P225/70R15	100T	60K	ORWL	10804	7.5 - 6	9 on 6.5	27.4	12	758	1594@44	580/A/B	
P235/70R15	102T	60K	ORWL	30023	8 - 6	9.5 on 7	28	12	743	1724@44	580/A/B	
P265/70R15	110T	60K	ORWL	10117	9 - 7	10.7 on 8	29.7	12	702	2125@44	580/A/B	
P215/75R15	100T	60K	ORWL	32459	7 - 5.5	8.5 on 6	27.7	12	751	1584@44	580/A/B	
P225/75R15	102T	60K	ORWL	41881	7.5 - 6	8.8 on 6	28.3	12	735	1704@44	580/A/B	
P235/75R15/XL	108T	60K	ORWL	04893	8 - 6	9.3 on 6.5	28.9	12	721	1985@50	580/A/B	
P265/75R15	112T	60K	ORWL	93100	9 - 7	10.5 on 7.5	30.7	12	678	2245@44	580/A/B	
P255/65R16	106T	60K	BSW	95489	9 - 7	10.2 on 7.5	29.1	12	716	1904@44	580/A/B	
P215/70R16	99T	60K	ORWL	15953	7 - 5.5	8.7 on 6.5	27.9	12	746	1554@44	580/A/B	
P225/70R16	101T	60K	ORWL	14809	7.5 - 6	9 on 6.5	28.4	12	732	1654@44	580/A/B	
P235/70R16	104T	60K	ORWL	29909	8 - 6	9.5 on 7	29	12	718	1804@44	580/A/B	
P245/70R16	106T	60K	ORWL	12469	8 - 6.5	9.8 on 7	29.5	12	704	1904@44	580/A/B	
P255/70R16	109T	60K	ORWL	32378	8.5 - 6.5	10.2 on 7.5	30.1	12	691	2065@44	580/A/B	
P215/75R16	101T	60K	ORWL	27133	7 - 5.5	8.5 on 6	28.7	12	726	1654@44	580/A/B	
P225/75R16/XL	106T	60K	ORWL	24706	7.5 - 6	8.8 on 6	29.3	12	710	1904@50	580/A/B	
P235/75R16/XL	109T	60K	ORWL	22027	8 - 6	9.3 on 6.5	29.8	12	697	2065@50	580/A/B	
P245/75R16	109T	60K	ORWL	14340	8 - 6.5	9.8 on 7	30.5	12	683	2065@44	580/A/B	
P265/75R16	114T	60K	ORWL	23207	9 - 7	10.5 on 7.5	31.7	12	657	2365@44	580/A/B	
P235/60R17	100T	60K	BSW	29509	8.5 - 6.5	9.5 on 7	28.1	12	740	1604@44	580/A/B	
P275/60R17	110T	60K	ORWL	30536	9.5 - 7.5	11 on 8	30	12	693	2125@44	580/A/B	
P235/65R17	103T	60K	ORWL	18701	8.5 - 6.5	9.5 on 7	29.1	12	716	1754@44	580/A/B	
P245/65R17	105T	60K	ORWL	32131	8.5 - 7	9.8 on 7	29.5	12	704	1854@44	580/A/B	
P255/65R17	108T	60K	ORWL	08921	9 - 7	10.2 on 7.5	30.1	12	691	2005@44	580/A/B	
P265/65R17	110T	60K	BSW	08549	9.5 - 7.5	10.7 on 8	30.6	12	681	2125@44	580/A/B	
P235/70R17/XL	108T	60K	BSW	30718	8 - 6	9.5 on 7	30	12	693	2005@50	580/A/B	
P245/70R17	108T	60K	ORWL	31653	8 - 6.5	9.8 on 7	30.6	12	681	2005@44	580/A/B	
P255/70R17	110T	60K	ORWL	12487	8.5 - 6.5	10.2 on 7.5	31.1	12	669	2125@44	580/A/B	
P265/70R17	113T	60K	ORWL	21567	9 - 7	10.7 on 8	31.7	12	657	2305@44	580/A/B	
P235/75R17	108T	60K	BSW	34949	8 - 6	9.3 on 6.5	30.9	12	674	2005@44	580/A/B	
P235/65R18	104T	60K	BSW	30080	8.5 - 6.5	9.5 on 7	30	12	692	1804@44	580/A/B	
P265/70R18	114T	60K	ORWL	06615	9 - 7	10.7 on 8	32.6	12	637	2365@44	580/A/B	
P275/55R20	111T	60K	BSW	28531	9.5 - 7.5	11.2 on 8.5	31.9	12	652	2185@44	580/A/B	
P275/60R20	114T	60K	BSW	32247	9.5 - 7.5	11 on 8	33	12	630	2365@44	580/A/B	
215/70R16	100H	50K	BSW	07127	7 - 5.5	8.7 on 6.5	27.9	11.5	746	1604@44	440/A/A	
255/60R17	106V	40K	BSW	34456	9 - 7	10.2 on 7.5	29.1	11.5	716	1904@44	440/A/A	
225/65R17	102H	50K	BSW	48275	8 - 6	9 on 6.5	28.5	11.5	730	1704@44	440/A/A	
235/65R17	104H	50K	BSW	80976	8.5 - 6.5	9.5 on 7	29.1	11.5	716	1804@44	440/A/A	
235/55R18	100V	40K	BSW	39138	8.5 - 6.5	9.7 on 7.5	28.2	11.5	739	1604@44	440/A/A	
255/55R18	105V	40K	BSW	22371	9 - 7	10.4 on 8	29	11.5	717	1854@44	440/A/A	
235/60R18	103V	40K	BSW	06598	8.5 - 6.5	9.5 on 7	29.1	11.5	715	1754@44	440/A/A	
245/60R18	105H	50K	BSW	02829	8.5 - 7	9.8 on 7	29.6	11.5	703	1854@44	440/A/A	

XL=Extra Load

* Passenger sizes used in Light Truck/SUV applications have reduced load capacity. This will differ from the maximum load branded on the tire sidewall. Government UTQG Ratings do not apply to Light Truck tires that are LT metric or flotation size.

ETEC™ not used on all sizes.