

BFGOODRICH® RADIAL T/A

Tire Size	Service Description	Limited Warranty	Side-wall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width (inches)	Overall Diameter (inches)	Tread Depth (in/32nds)	Rev/Mile @45 mph	Max Load Single (lbs@psi)	UTQG	O.E. Fit-ments
P215/60R14	91S	Std	RWL	67439	7.5 - 6	8.7 on 6.5	24.2	11	861	1345@35	400/A/B	
P225/60R14	94S	Std	RWL	68581	8 - 6	9 on 6.5	24.7	11	842	1455@35	400/A/B	
P235/60R14	96S	Std	RWL	61144	8.5 - 6.5	9.5 on 7	25.1	11	829	1565@35	400/A/B	
P245/60R14	98S	Std	RWL	96965	8.5 - 7	9.8 on 7	25.6	11	813	1675@35	400/A/B	
P205/70R14	93S	Std	RWL	37157	7 - 5	8.2 on 6	25.4	12	821	1433@35	400/A/B	
P215/70R14	96S	Std	RWL	64077	7 - 5.5	8.7 on 6.5	25.9	12	803	1554@35	400/A/B	
P225/70R14	98S	Std	RWL	37137	7.5 - 6	9 on 6.5	26.5	12	786	1675@35	400/A/B	
P295/50R15	105S	Std	RWL	16225	10.5 - 8	12.2 on 9.5	26.6	11	780	2061@35	400/A/B	
P195/60R15	87S	Std	RWL	84420	7 - 5.5	7.9 on 6	24.2	11	859	1190@35	400/A/B	
P205/60R15	90S	Std	RWL	71599	7.5 - 5.5	8.2 on 6	24.7	11	842	1301@35	400/A/B	
P215/60R15	93S	Std	RWL	71715	7.5 - 6	8.7 on 6.5	25.2	11	827	1411@35	400/A/B	
P225/60R15	95S	Std	RWL	03175	8 - 6	9 on 6.5	25.6	11	813	1521@35	400/A/B	
P235/60R15	98S	Std	RWL	09082	8.5 - 6.5	9.5 on 7	26.1	11	797	1642@35	400/A/B	
P245/60R15	100S	Std	RWL	98854	8.5 - 7	9.8 on 7	26.6	11	782	1753@35	400/A/B	
P255/60R15	102S	Std	RWL	57931	9 - 7	10.2 on 7.5	27.1	11	769	1885@35	400/A/B	
P275/60R15	107S	Std	RWL	17476	9.5 - 7.5	11 on 8	28	11	743	2149@35	400/A/B	
P215/65R15	95S	Std	RWL	16664	7.5 - 6	8.7 on 6.5	26	10.5	799	1510@35	400/A/B	
P215/70R15	97S	Std	RWL	26613	7 - 5.5	8.7 on 6.5	26.9	12	774	1620@35	400/A/B	
P225/70R15	100S	Std	RWL	58541	7.5 - 6	9 on 6.5	27.4	12	758	1753@35	400/A/B	
P235/70R15	102S	Std	RWL	79673	8 - 6	9.5 on 7	28	12	743	1896@35	400/A/B	
P255/70R15	108S	Std	RWL	94081	8.5 - 6.5	10.2 on 7.5	29.1	12	715	2183@35	400/A/B	
P155/80R15	83S	Std	RWL	06462	5.5 - 4.5	6.2 on 4.5	24.8	12	840	1069@35	400/A/B	