

E4-WM5-Y189A01 MOUNTING INSTRUCTION



ø 30

Material- Nr. Part no.	VA FRONT	HA REAR	A mm	B mm	C mm	D	
						Nm	ft lb
R30-5014			43	-	-	25	19
R30-5015		X	43	-	-	25	19
R30-5016	X		43		-	25	19
R30-5019	X		43	-	-	25	19
R30-5020			43	-	-	25	19
R30-5021		X	35	336	344	25	19
R30-5026	X		-	256	271	25	19
R30-5028	X		47	309	324	25	19
R30-5029		X	39	324	339	25	19
R30-5031	X		43	337	352	25	19
R30-5032		X	40	316	331	25	19
R30-5033		X	38	362	377	25	19
R30-5035		X	52	328	343	25	19
R30-5036	X		45	266	280	25	19
R30-5039	X		86	270	285	25	19
RE2-5045	X		28	298	313	25	19
RE2-5047		X	39	326	341	30	23
RE2-5048	X		40	273	288	30	23
R36-5013	X		43	-	-	25	19
RE2-5051	X		44	265	280	25	19
RE2-5052		X	40,5	297	312	25	19
RE2-5053	X		46	274	289	25	19
RE2-5054		X	46	293	308	25	19
RE2-5055	X		33,5	295	310	25	19
RE2-5056		X	31,5	369	384	25	19
RE2-5057	X		36,5	286	301	30	23
RE2-5058		X	29	341	356	30	23
RE2-A153 2)	X		47	341	356	25	19
RE2-61029	X		39	285	300	25	19
RE2-61030		X	43	297	312	25	19

E4-WM5-Y189A01 MOUNTING INSTRUCTION



ø 36

Material- Nr. Part no.	VA FRONT	HA REAR	A mm	B mm	C mm	D	
R36-5013	X		43	-	-	25	19
R36-5022	X		48	-	-	25	19
R36-5023	X		43	-	-	25	19
R36-5027		X	-	335	350	25	19
R36-5034	X		15	245	260	25	19
RE3-5046	X		42	335	350	25	19
RE3-A165 1)	X		50	317	332	25	19

- 1) is suitable for original and KYB New SR special strut
- 2) before fitment original strut outer tube must be flared by special tool