

SPECIFICATIONS

FEATURES / SPECS	
MOTOR	PREMIUM 6.0HP SERIES WOUND
SWITCH	500A SEALED CONTACTOR
THERMAL LIMITER	MOTOR OVERHEAT PROTECTION WITH LED FEEDBACK LIGHT & AUTO RECONNECT
CONTROLLER	WIRED: HAND CONTROL WITH 12' LEAD INCLUDED WIRELESS: OPTIONAL & AVAILABLE 20156
POWER UNIT	REMOTE MOUNTABLE
BATTERY LEADS	6' W/HIGH HEAT/ABRASION RESISTANT SHEATHING
GEAR TRAIN	3 STAGE PLANETARY
GEAR RATIO	216:1
GEAR BOX	CLOCKABLE TO ROTATE SHIFTER (contact for instructions)
CLUTCH	FREESPOOLING
BRAKE	AUTOMATIC LOAD HOLD IN DRUM
DRUM DIA x L	2.5" X 9" (64 X 228mm)
OVERALL DIMENSIONS (LxWxH)	22 X 6.6 X 8.4" (584 X 168 X 214mm)
MOUNTING BOLT PATTERN	10 X 4.5"
WARRANTY	LIMITED LIFETIME
BATTERY RECOMMENDATION	650CCA

PULL, SPEED, AMPS

LINE PULL LBS	LINE SPEED FT/MIN	CURRENT A
0	35.4	80
2000	17.1	140
4000	13	200
6000	9.8	260
8000	8	310
9300	7.2	350

LINE PULL AND ROPE CAPACITY IN LAYER

LAYER	RATED LINE PULL LBS	TOTAL ROPE ON DRUM FT
1	9300	19.6
2	8000	43
3	7200	72
4	6000	100